

HE Series

Modular Headend System - AMCM-860



The AMCM-860 is a professional quality agile audio/video modulator with an output frequency range of 54-860 MHz. It joins Blonder Tongue's family of modular headend components and works in conjunction with the MIRC-12V rack chassis and MIPS-12C power supply.

The unit provides a modulated aural & visual carrier on any channel in the 54 to 860 MHz range. Frequency plans including Standard CATV, IRC, HRC and Broadcast are accommodated via front panel selection. Channel tuning is easily accomplished with the use of front panel switches following the entry instructions. All channels with appropriate FCC offsets are pre-programmed and tuned electronically via microprocessor.

The unit accepts any standard audio/video source such as satellite receivers, television camera, video tape recorders or demodulators. The advanced design ensures access for all level and over-modulation controls via the front panel with LED indicators for each. Internal selectable jumper settings allow for compatibility of features such as defeatable audio pre-emphasis for BTSC compatibility.

Special features have been built into the unit firmware to ensure the best possible user experience. This includes the ability to alert an operator to any inadvertent or designed change to the unit switches by flashing a red error indicator. The indicator will continue to flash until the condition is corrected or the unit is reset.

○ Features & Benefits

- Meets FCC Docket 21006 Aeronautical Frequency Offset Requirements
- Fully Compatible With BTSC Encoded Stereo Audio
- Three Year Warranty
- Front Panel Accessible Level Controls for Easy Set-Up and Adjustments
- Die-Cast Chassis Offers Superior Protection Against Ingress or Egress
- Supports All Broadcast and CATV Channels, Including HRC and IRC Assignments from 54 to 860 MHz

○ Specifications

RF

Frequency Range: 54-860 MHz
Channels: CATV, VHF, UHF (STD,HRC,IRC)
FCC Offset (pre-programmed):
0, +12.5, or 25 kHz
Output Level - Min: +45 dBmV
Output Level Adjust: 15 dB
Aural/Visual Carrier Ratio: -10 to -17 dB
Visual Carrier Frequency Tolerance
Standard Channels: ± 5 kHz
FCC Aeronautical Channels: ± 3 max kHz
4.5 MHz Aural Inter Carrier Frequency: ± 1 Hz
Channel Selectivity:
Adjacent Aural and Below: -40 dB
Adjacent Picture and Above: -50 dB
Spurious Outputs: -60 dBc
C/N Ratio In Channel: 65 dB
Broadband Noise: -76 dBc
Output Impedance: 75 ohm
Output Return Loss: 12 dB

Video

Input Level: 1.0 V p-p
Frequency Response
fv-0.5 MHz to fv+4.2 MHz: ± 1.0 dB
P-P Video to RMS Hum Ratio: 65 dB
Video Signal-to-Noise Ratio,
NTC-7 Weighted: 62 dB
Differential Gain: 2.0 %
Differential Phase: 1.0 °
Over Modulation Indicator: 87.5, ± 2.5 %
Input Impedance: 75 ohm
Input Return Loss: 24 min, dB

Audio

Input Level: 140 mV RMS
Ext. 4.5 MHz Input Level: 40 ± 1 dBmV
Frequency Range: 20 Hz to 20 kHz

Pre-Emphasis-Mono: 75 μ s
Frequency Response: ± 1.0 dB
IF Pre-Emphases defeated: +0.5 dB
Audio Signal-to-Noise: 58 dB
Total Harmonic Distortion: 0.6 %
Over Modulation Indicator: 25, ± 2 kHz
Input Impedance: Greater than 10k Ω , unbalanced

General

Power Requirements
Voltage: +12, +5 VDC
Power: 5 W
Temperature Range: 0 to +50 °C
Current: 235, 375 mA

Mechanical

Dimensions (WxHxD):
1.15 x 3.5 x 7.5 in
29 x 89 x 101 mm
Weight: 0.8 lbs, .36 kg

Connectors (Rear Panel)

Video Input: "F" Type, Female
Audio Input: RCA Phono
RF Output: "F" Type Female

Controls (Front Panel)

Frequency Selection: Push-Button Switches
Video Level: Control
A/V Ratio: Control
Audio Level: Control
RF Output Level: Control
Channel Enter: Push Button

Indicators (Front Panel)

Power ON: 2 color LED, Red/Green
Video Over Modulation: LED, Red
Audio Over Modulation: LED, Red

Refer to product instruction manual for additional specification measurements and notes.

○ Ordering Information

Model	Stock No.	Description
AMCM-860	7766A	Modular Agile Audio/Video Modulator (HE 12 Series) +45 dBmV, 54-860 MHz Agile
AMCM-860H	7766HA	Modular Agile Audio/Video Modulator (MIRC-4 Series) +45 dBmV, 54-860 MHz Agile

Available through

Multicom, Inc.

1076 Florida Central Parkway, Longwood, FL 32750

Ph: 407-331-7779 Toll Free: 800-423-2594 Fax: 407-339-0204

www.multicominc.com

multicom@multicominc.com