



Multicom RG-6 90% Braid Messenger Drop Cable

Description

Multicom's RG6 coax cable is ideal for RF applications including outdoor TV antennas, cable television, and satellite distribution. The coaxial messenger cable includes an integrated .051 inch messenger wire for support in aerial installations. Cable jacket is a black PVC for environmental protection.



Key Features

- ◇ .051 messenger wire for aerial support
- ◇ Copper covered steel center conductor
- ◇ Gas expanded polyethylene dielectric
- ◇ Swept to 3,500 MHz
- ◇ Aluminum-polypropylene-aluminum laminated tape with overlap bonded to dielectric
- ◇ Jacket: PVC
- ◇ Braid: 90% aluminum
- ◇ 1,000 foot reels

Attenuation (@68° F / 20°C)

Frequency (MHz)	Max (dB/100ft.)	Max (dB/100m)
5	0.58	1.90
55	1.60	5.25
450	4.40	14.43
750	5.65	18.54
1000	6.55	21.49
1750	8.88	29.13
2000	9.38	30.78
3000	11.60	38.06
3500	12.82	42.05

M690-BVM

www.multicominc.com

Multicom, Inc.

Ph: 800-423-2594

Fax: 407-339-0204

Email: multicom@multicominc.com



Multicom RG6-90 Messenger Drop Cable

Product Specifications

Key Features

- ◇ 18 AWG copper covered steel center conductor
- ◇ Gas expanded polyethylene dielectric
- ◇ 1,000 foot reels
- ◇ Swept to 3,500 MHz
- ◇ Aluminum-polypropylene-aluminum laminated tape with overlap bonded to dielectric
- ◇ 90% aluminum braid
- ◇ Jacket: PVC

Specifications

Physical Dimensions	Inches	mm
Nominal Center Conductor Diameter	0.040	1.02
Nominal Diameter Over Dielectric	0.180	4.57
Nominal Diameter Over First Shield (Tape)	0.187	4.75
Nominal Diameter Over Jacket	0.278	7.06
Nominal Jacket Wall Thickness	0.030	0.76
Nominal Diameter of Steel Messenger	0.051	1.30
Mechanical Characteristics	Lbs.	Kgs.
Minimum Breaking Strength of Messenger	180	82
Electrical Characteristics		
Nominal Impedance	75 ohms	
Nominal Velocity of Propagation	85%	

Attenuation (@68° F / 20°C)

Frequency (MHz)	Max (dB/100ft.)	Max (dB/100m)
5	0.58	1.90
55	1.60	5.25
450	4.40	14.43
750	5.65	18.54
1000	6.55	21.49
1750	8.88	29.13
2000	9.38	30.78
3000	11.60	38.06
3500	12.82	42.05

Description

Multicom's RG6 coaxial cable for aerial applications includes an integrated .051 inch messenger wire for support in aerial installations. Cable jacket is a black PVC for environmental protection.

M690-BVM

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204
Email: multicom@multicominc.com