



Multicom 1310nm Optical Transmitter

Key Features

- » Transmits NTSC, PAL, ATC, and related digital information for CATV and/or telephony applications
- » Available in a variety of output levels
- » High linearity, optically isolated, distributed AM feedback DFB laser.
- » 54-1000MHz RF input bandwidth
- » Front panel RF test point (-20dB)
- » Operation wavelength: 1310nm
- » Low RF drive levels enabled due to built-in RF amplifier and Automatic Gain Control
- » Microprocessor-controlled diagnostics, front panel LCD display and controls
- » Optional integrated SNMP network interface
- » Dual online redundant power supplies



Description

Multicom's MUL-1310TX-1000-X Direct Modulated Transmitter delivers high performance signal transmission of NTSC, PAL, ATC, QAM, and related digital information for CATV and/or telephony applications. It is based upon custom high-linearity optically isolated DFB (Distributed Feedback) lasers, specifically designed for multi-channel AM video applications. The built-in control circuits provide an exceptionally low noise and inter-modulation characteristics. Automatic output power control, coupled with temperature stabilization provided by a thermoelectric cooler ensures maximum performance and longer laser life.

The units are packaged in slim 1.75-inch high (1RU), 19-inch aluminum rack-mounted enclosures. Each unit is fitted with redundant self-contained power supplies with 90-265VAC inputs.

All internal laser parameters and monitoring functions are under microprocessor control: the front panel displays status information related to laser operation, temperatures, and RF input.

MUL-1310TX-1000-x

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204
Email: multicom@multicominc.com