



Multicom

Optical Return Path Receiver

Product Specifications

Description

The Multicom MUL-HRPR-4B Optical Return Path Receiver is ideally suited for use in optical headends in HFC and FTTH and many other fiber optic-based data, video, and voice networks, including Broadband Stimulus and FCC National Broadband projects and applications, and provides a cost effective solution.

The MUL-HRPR-4B's state-of-the-art features include an industry-leading 4 port, 30 - 60dBmV individually adjustable RF outputs, 5 - 200MHz return bandwidth, wide optical input range down to -9dBm, and a unique backlit front panel control display - all in a temperature-controlled, 1 RU rack-mount chassis.

Technical Specifications

	Specifications	Values	Notes
General	Operating temp. (°C)	0 - 50	32 - 122°F
	Storage temp. (°C)	-40 - 85	
	Operating relative humidity (%)	5 - 95	Non-condensing
	Power Supply - 9 Volt AC	90 - 265	
	Power Consumption (W)	48	4 receivers
	Size (inches - WxDxH)	19 x 12 x 1.75	
	Interface port	RJ45, RS232	
Optical	Wavelength (nm)	1200 - 1620	
	Responsivity (A/W)	0.85	At 1310nm
	Input power level (dBm)	-9 - +1	
	Return loss (dB)	50	
	Output fiber connector	SC/APC	
RF	RF Bandwidth (MHz)	5 - 200	
	RF output level (dBmV)	30 - 60	
	RF gain adjustment range (dB)	-30 - 0	1 dB steps
	Flatness (dB)	-0.75 - +0.75	
	Return loss (dB)	16	75Ω impedance
	RF connector (Main input)	F type	
	NPR (dB)	41	DFB LD with 15 dB link loss

MUL-HRPR-4B

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204
Email: multicom@multicominc.com