

LOOP LEAD-IN CABLE

IMSA Specification 50-2 Loop Lead-In Cable



Cable Identification

Indent print on jacket
 "ADVANCED DIGITAL CABLE
 YYYY IMSA 50-2 600V"

**replace YYYY with year of manufacturer*

Specifications		Color Code	Put-Ups
Conductor - Stranded Tinned Copper per ASTM B-8, B-33 Insulation - 18 AWG - .030" PE 16 AWG - .030" PE 14 AWG - .030" PE 12 AWG - .030" PE	Shielding - Aluminum Jacket - Polyethylene Voltage Rating - 600 V Temp. Rating - 75°C	Clear/Black (1 Pair Types) See Color Code Tables on Page 15 for Multi-Pair Cables	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory represen- tative for availability.</i>

PART NO.	AWG	NO. OF PAIRS	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
			INCH	mm	INCH	mm	
18 AWG							
8740	18	1	.030	.762	.286	7.26	29
8742A	18	2	.030	.762	.322	8.19	54
8743A	18	3	.030	.762	.465	11.81	78
16 AWG							
8750	16	1	.030	.762	.292	7.42	38
14 AWG							
8780	14	1	.030	.762	.332	8.43	55
8782A	14	2	.030	.762	.400	10.16	102
8783A	14	3	.030	.762	.566	14.38	120
8784A	14	4	.030	.762	.584	14.83	171
12 AWG							
8790	12	1	.030	.762	.356	9.04	75