


TUBE LOOP DETECTOR CABLE

IMSA Specification 51-5 Tube Loop Detector Cable



Cable Identification


Indent print on jacket
“ADVANCED DIGITAL CABLE,
INC. YYYY IMSA 51-5
600V”

*replace YYYY with year of manufacturer

Specifications		Color Code	Put-Ups
Conductor - Stranded Bare Copper per ASTM B-3, B-8	Insulation - PVC/Nylon 14 AWG - .015" + .05 Nylon 12 AWG - .015" + .05 Nylon	Black, Orange <i>Other colors available upon request.</i>	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
Voltage Rating - 600 V Temp. Rating - 75°C	Jacket - PVC or HDPE 14 AWG - .030" 12 AWG - .030"		

PART NO.	AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
PVC						
8450	14	.030	.762	.250	6.35	30
8480	12	.030	.762	.250	6.35	36
HDPE						
8450PE	14	.030	.762	.250	6.35	22
8480PE	12	.030	.762	.250	6.35	29

IMSA Specification 51-7 Tube Loop Detector Cable



Cable Identification

Indent print on jacket
“ADVANCED DIGITAL CABLE,
INC. YYYY IMSA 51-7 600V”

*replace YYYY with year of manufacturer

Specifications		Color Code	Put-Ups
Conductor - Stranded Bare Copper per ASTM B-3, B-8	Insulation - XLPE 14 AWG - .030" 12 AWG - .030"	Black, Orange <i>Other colors available upon request.</i>	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
Voltage Rating - 600 V Temp. Rating - 75°C	Jacket - PVC or HDPE 14 AWG - .030" 12 AWG - .030"		

PART NO.	AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
PVC						
8460XL	14	.030	.762	.191	4.85	31
8470XL	12	.030	.762	.213	5.33	36
HDPE						
8460XLP	14	.030	.762	.191	4.85	26
8470XLP	12	.030	.762	.213	5.33	31

Purchase from Multicom  www.multicominc.com | 800-423-2594

