



LL-400s



LL-400s installed in pedestal

LightLink™ LL-400s Optical Splicing and Distribution Enclosure

The LL-400s Fiber Optic Splicing and Distribution Enclosure provides for organizing, splicing, and interconnecting fibers in FTTx, broadband, distribution, and building entrance applications. Each LL-400s enclosure features a scratch resistant powder coated aluminum base and a fully gasketed cover. A unique self-sizing grommet design allows for express and preterminated cable installation. The LL-400s is a butt-style enclosure equipped with four independent cable entry/exit grommets, used for outdoor pedestal or indoor building entrance and riser splicing applications. The unit supports a maximum storage and splicing capacity of up to 72 single or 144 mass-fused fibers.

Features

- Independent cable strain relief system
- Cable entry/exit grommet seals
- Removable Hinged Front Cover
- Fiber routing system
- Splice tray support system
- 72 single fusion splices
- 144 mass fusion splices

Specifications

PARAMETER	VALUE
Material	Chassis – aluminum
Coatings	Electrostatically applied, powder coat
Color	Antique white
Dimensions (H x W x D) in. (cm)	21.63 x 6.63 x 3.25 (54.94 x 16.84 x 8.26)
Weight lbs. (kg)	4.74 (1.77)

Ordering Information

DESCRIPTION	PART #
LL-400s	FM000639
LL-400s with (2) multi-drop grommets	FM000618
LL-400s in 1010 Pedestal	FM000777

Accessories

DESCRIPTION	PART #
LL-400b Pedestal Spacer Mount Kit	911740-00-00
LL-4848 Mass Fusion Splice Tray	911437-00-02
LL-2448 Universal Splice Tray	911289-00-02
LL-2400 Single Fusion Splice Tray	91710-06