

F - FEMALE and MALE SPLICES

ZINC DIECAST F-SPLICES



AF-81M
FEMALE SPLICE
Cast Construction,
Machine threaded



AF-81NW
FEMALE SPLICE
W/Nut & Washer,



NW
NUT AND WASHER



AF-81B
FEMALE SPLICE
Machine threaded. All brass



AF-71
F-MALE SPLICE

DIGITAL F-SPLICE - HIGH RETURN LOSS - 5-2300 MHZ



AF-81GD
2 GHz Zinc Diecast Splice
Machine Threaded
28dB Return Loss
for 5-2300 MHz



AF-81G
2 GHz Brass Splice
28 dB High Return Loss
for 5-2300 MHz



AF-71G
F-MALE SPLICE
28dB Return Loss
for 5-2300 MHz

G GROUNDING BLOCKS - 1GHz and 2.3GHz type

ZINC DIECAST GROUND BLOCKS



GB-1
GROUNDING BLOCK
with Zinc Die-cast Splice



GB-2
GROUNDING BLOCK
with two Zinc Die-cast
Splices

FOR DUAL CABLE SYSTEM



GB-2D
DUAL GROUNDING BLOCK
with two zinc die-cast splices. Two holes
& set screws for separate ground wires.

PREMIER GROUNDING BLOCK SERIES - HIGH RETURN LOSS - 5-2300 MHZ



GB-1G
GROUNDING BLOCK
Brass Splice-Cast Base
28 dB Return Loss
5-2300 MHz



GB-1GD
GROUNDING BLOCK
Zinc Diecast Splice using
Circular Contact Pin 25-28 dB
Return Loss 5-2300 MHz



GB-2GD
GROUNDING BLOCK
With two Zinc Diecast
Splices using Circular
Contact Pin 25-28 dB
Return Loss - 5-2300 MHz



GB-3GD
DUAL BLOCK
Two 4 m/m holes and
set screws for two
separate ground wires
28dB Return Loss 5-2300 MHz

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Order From: **MULTICOM**

Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com