

INSTALLATION ACCESSORIES

SECURITY SHIELDS AND TOOL



AST-1
SECURITY SHIELD TOOL
Use with SS-2S or SS-1T
Security Shields



SECURITY SHIELDS
SS-1T - 1-1/8" Metal
Screw-on Shield
SS-2S - 1-1/8" Metal
Slip-on Shield

LOCKING TERMINATORS



LT-1
LOCKING TERMINATOR
Aluminum Body
Impedance: 75 Ohm \pm 5%

SURGE PROTECTOR



PT-1
INLINE SURGE PROTECTOR
The PT-1 is ideal for protection from lightning for CATV converters, decoders, TV sets, VCR, Satellite receivers, or any other Electronics used at home or office.

COAXIAL RF A/B SWITCHES



ABS-1
COAXIAL A/B SWITCH
ECONOMY COAXIAL SWITCH



AB-4
A/B SWITCH - PUSH BUTTON TYPE



AB-5
HI-ISOLATION A/B SWITCH
Slide Lever Type



AB-95
A/B SWITCH - PUSH BUTTON TYPE

Features:

- High 90 dB ISOLATION exceeds FCC specifications.
- Heavy duty zinc die-cast inner housing.
- Double backed tape and mounting screws supplied.

Specifications:

| | ABS-1 | AB-4 | AB-5 | AB-95 |
|------------------------|-------------|------|------|-------|
| Frequency Range: | 5-1750 MHz | | | |
| Insertion Loss: | -0.7 dB Max | | | |
| Isolation: (dB Min.) | | | | |
| 5-1000 MHz | -60 | -90 | -90 | -90 |
| 1000-1750 MHz | -50 | -60 | -60 | -60 |
| Return Loss: (dB Min.) | | | | |
| 5-1000 MHz | -15 | -20 | -18 | -20 |
| 1000-1750 MHz | -13 | -16 | -15 | -16 |
| Number of Input: | 2 | 2 | 2 | 2 |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com