


Bekaert Strand Product Specifications

				Minimum Breaking Strength (lbs.)					Minimum Weight of Coating oz./sq. ft.		
Strand Diameter (inches)	Wires Per Strand	Coated Wire Diameter (inches)	Approx. Stand Weight/1000 ft (lbs.)	Utilities Grade	Common Grade	Siemens-Martin Grade	High Strength Grade	Extra High Strength Grade	Class A	Class B	Bezinal®
1/4	3	0.120	117	3150	1860	3040	4730	6740	0.85	1.70	0.85
1/4	3	0.120	117	4500	0	0	0	0	0.85	1.70	0.85
5/16	3	0.145	171	6500	2490	4090	6350	9100	0.90	1.80	0.90
3/8	3	0.165	220	8500	3330	5560	8360	11800	0.90	1.80	0.90
3/16	7	0.062	73	0	1150	1900	2850	3990	0.50	1.00	0.50
3/16	7	0.065	80	2400	0	0	0	0	0.50	1.00	0.50
7/32	7	0.072	98	0	1540	2560	3850	5400	0.50	1.00	0.50
1/4	7	0.080	121	0	1900	3150	4750	6650	0.60	1.20	0.60
9/32	7	0.093	164	4600	2570	4250	6400	8950	0.70	1.40	0.70
5/16	7	0.104	205	0	3200	5350	8000	11200	0.80	1.60	0.80
5/16	7	0.109	225	6000	0	0	0	0	0.80	1.60	0.80
3/8	7	0.120	273	11500	4250	6950	10800	15400	0.85	1.70	0.85
7/16	7	0.145	399	18000	5700	9350	14500	20800	0.90	1.80	0.90
1/2	7	0.165	517	25000	7400	12100	18800	26900	0.90	1.80	0.90
9/16	7	0.188	671	0	9600	15700	24500	35000	1.00	2.00	1.00
1/2	19	0.100	504	0	7620	12700	19100	26700	0.70	1.40	0.70
9/16	19	0.113	637	0	9640	16100	24100	33700	0.80	1.60	0.80
5/8	19	0.125	796	0	11000	18100	28100	40200	0.85	1.70	0.85
3/4	19	0.150	1155	0	16000	26200	40800	58300	0.90	1.80	0.90

Bekaert Corporation



All Bekaert plants that produce Bekaert Strand products hold a ISO 9001 certificate.



Superior Coating Technology

Bezinal is Bekaert's industry leading coating technology with unsurpassed corrosion resistance. Bezinal is a 95% Zinc + 5% Aluminum (+Mischmetal) eutectic alloy that exhibits remarkable corrosion resistant properties by combining passivation corrosion characteristics present with aluminum together with the sacrificial protection offered by the zinc content of the alloy. With superior formability, longevity, and durability, Bezinal is an ideal solution to your wire needs.

Purchase from Multicom  www.multicominc.com | 800-423-2594