

AP Series

Agile Heterodyne Processors



○ Features & Benefits

- EAS/ALT IF Ready Via Manual or Automatic Mode
- Superior Broadband Noise Performance (-76 dB)
- C-UL Listed, Three Year Warranty
- Front Panel Accessible Level Controls for Easy Set-Up and Adjustments
- Rack Mountable - 1 EIA (1.75") Rack Space

The AP Series are professional quality, agile heterodyne processors equipped with the Emergency Alert System (EAS) feature, which can also be used as an alternate IF input. These units convert any channel in the 50 to 806 MHz (7 to 43 MHz with Option 17) frequency range to any channel in the 50 to 550/750 MHz (7 to 550/750 MHz with Option 04) frequency range.

The AP Series is ideal for moving an off-air channel (VHF or UHF) or any single channel source to any unused channel (broadcast or CATV, including HRC and IRC assignments) in the system. Agile channel selection permits on-the-fly channel changes and reduces the need for large inventories of channelized products. Channel selection is accomplished with the use of simple to use front panel accessible dip switches. These processors have wide range of standard and optional features that make them very suitable for advanced CATV systems. Four models are available with different output level and frequency ranges and a variety of options.

All models feature rock solid, synthesized frequency control, with a tuning increment of 250 kHz. True vestigial sideband SAW filtering guarantees superior broadcast picture quality. Two SAW filters are used to ensure proper adjacent channel rejection. Delayed AGC circuitry automatically compensates for input signal variations. These processors have an external IF loop, which allows interfacing with video all-call and signal scrambling systems. The AP Series utilizes a standby carrier oscillator to provide a blank picture when the input level drops below usable level. This prevents a snowy picture from being delivered to the distribution network in the event of signal degradation or complete loss of picture. The EAS/ALT IF feature allows the customer to choose between manual and automatic selection of EAS/ALT IF input signal.

These processors provide extremely clean output signals with distortion products (-60 dB or better). An exceptionally low broadband noise floor (-76 dBc or better) makes the AP Series ideal for large, multiple channel headends without the need for additional filtering.

Available through **Multicom, Inc.**

1076 Florida Central Parkway, Longwood, FL 32750

Ph: 407-331-7779 Toll Free: 800-423-2594 Fax: 407-339-0204

www.multicominc.com

multicom@multicominc.com

AP Series

Agile Heterodyne Processors

○ Specifications

RF

Input Frequency Range
Standard: 54-88 & 108-806 MHz
Option 17 - Sub-band Input: 7-49 MHz
Input Channels: SUB, VHF, UHF, CATV (STD,HRC)
Output Frequency Range
AP-40-550 & AP-60-550: 50-450 MHz
AP-40-750 & AP-60-750: 50-550 MHz
Option 04: AP-40-450 & AP-60-450: 7-450 MHz
Output Channels: SUB, CATV (STD,HRC,IRC)
Tuning Increment: 250 kHz
FCC Offset: 0, +12.5, or +25 kHz
Input Level Range: -18 to +30 dBmV
AGC Stiffness: 1.0 dB
Output Level - Min
AP-40-550 & AP-40-750: +40 dBmV
AP-60-550 & AP-60-750: +60 dBmV
Output Level Adjust: 10 dB
Noise Figure
VHF: 8 dB
UHF: 10 dB
Aural/Visual Carrier Ratio: 0 to -10 dB
Visual Carrier Frequency Tolerance
Standard Channels: ± 10 kHz
FCC Aeronautical Channels: ± 3 kHz
Channel Selectivity:
Adjacent Aural and Below: -65 dB
Adjacent Picture and Above: -65 dB
Spurious Outputs: -60 dBc
Intermod Distortion: -64 dB
Broadband Noise: -76 dBc
Image Rejection: 65 dB
Bandpass Flatness f_v to $f_v+4.5$ MHz: ± 1.0 dB
Input/Output Impedance: 75 ohm
Input Return Loss: 12 dB
Output Return Loss: 14 dB

IF

Aural Frequency: 41.25 MHz
Visual Frequency: 45.75 MHz
Composite IF Loop Output
Aural Carrier Level: +13 dBmV
Visual Carrier Level: +28 dBmV
Output/Input Impedance: 75 ohm
Output Return Loss: 12 dB
Input Return Loss: 12 dB
EAS/ALT IF Input Level: 28 dBmV @ 45.75 MHz
EAS/ALT IF Switch Isolation: >60 dB

General

Power Requirements
Voltage: 117, $\pm 10\%$ VAC
Frequency: 60 Hz
Power - AP-40-450 & AP-40-550: 20 W
Power - AP-60-450 & AP-60-550: 24W
Fuse: 3/8 A
Temperature Range: 0 to +50 °C

Mechanical

Dimensions (WxHxD)
AP-40-550 & AP-40-750:
19.0 x 1.75 x 9.75 in.
483 x 44 x 248mm
AP-60-550 & AP-60-750:
19.0 x 1.75 x 14.25 in.
483 x 44 x 362 mm
Weight
AP-40-550 & AP-40-750: 8 lbs. (3.64 kg)
AP-60-550 & AP-60-750: 9 lbs. (4.09 kg)

Connectors (Rear Panel)

RF Input
Standard - VHF/UHF: "F" Type, Female
Option 17: Sub-band Input: "F" Type, Female
IF Output: "F" Type, Female
IF Input: "F" Type, Female
RF Output: "F" Type, Female
Serial Data Input & Output Option 20: Serial
Input: RJ-12, Female
EAS/ALT IF: "F" Type, Female

Controls (Front Panel)

Frequency Selection
Input: DIP Switches
Output: DIP Switches
Frequency Response Adjust: Controls
Aural Carrier Level: Control
Frequency Fine Tune: Control
FCC Offset Selection Option 12: ABOC:
DIP Switches
RF Output Level: Control

Controls (Top Cover & Rear Panel)

Standby Oscillator Threshold Adjust: Control
Sub-band Input Channels Option 17:
Slide Switch
EAS/ALT IF: 3 Position, Terminal Strip

Indicators (Front Panel)

Power ON: LED, Green
EAS/ALT IF: LED, Green

Refer to product instruction manual for additional specification measurements and notes.

○ Ordering Information

Model	Stock No.	Description
AP-40-550B	59802	Agile Heterodyne Processor with EAS +40 dBmV, 54-88/108-806 MHz Input, 50-550 MHz Output
AP-40-750B	59803	Agile Heterodyne Processor with EAS +40 dBmV, 54-88/108-806 MHz Input, 50-750 MHz Output
AP-60-550B	59817	Agile Heterodyne Processor with EAS +60 dBmV, 54-88/108-806 MHz Input, 50-550 MHz Output
AP-60-750B	59818	Agile Heterodyne Processor with EAS +60 dBmV, 54-88/108-806 MHz Input, 50-750 MHz Output

Accessories

Model	Stock No.	Description
AP-OPT 04	59804	AP Series Option: Sub-Band Output
AP-OPT 12	59122	AP Series Option: Automatic Broadcast Offset Correction
AP-OPT 14	59144	AP Series Option: On Channel-lock
AP-OPT 17	59177	AP Series Option: Sub-Band Input, 7-49 MHz
AP-OPT 20	59200	AP Series Option: Digital Control, Serial RS-232

Available through **Multicom, Inc.** 1076 Florida Central Parkway, Longwood, FL 32738

Ph: 407-331-7779 Toll Free: 800-423-2594 Fax: 407-339-0204

www.multicominc.com