CDSR Series

Commercial Digital Satellite Receiver



- C/Ku Band Compatible 950 to 1550 MHz Digital Satellite Receiver
- DigiCipher® II Encoding Compatible
- Supports Virtual Channing Mapping & Control via Extensive Software Menu
- UL Listed
- One Year Motorola Warranty



The CDSR-4400X is a professional quality, high performance, commercial digital satellite receiver. This unit is ideal for applications requiring an economically priced, commercial grade digital IRD. The CDSR-4400X is C and Ku band compatible, based upon DigiCipher® II encoding. It accepts signals in the 950 to 1550 MHz frequency range. Complete control of the CDSR-4400X is accomplished using extensive front-panel accessible menus.

The microprocessors and memory integrated into each CDSR-4400X decode and decompress the MPEG II video, audio, data and other information present in the signal, allowing significantly less information to be transmitted which reduces bandwidth requirements.

Specifications

RF

Frequency Range: 950 - 1550 MHz Isolation, Port to Port: 40 dB Impedance: 75 Ohm

Video

Frequency Response (NTSC): ±1.0 dB Frequency Response (PAL): ±1.0 dB Format: QQPSK & QPSK DigiCipher® II

Differential Gain: 5% p-p Differential Phase: 5° p-p Signal-to-Noise Ratio: 57 dB

Audio

Frequency Range: 20 Hz - 20 kHz
Frequency Response: ±1.3 dB
Output Level: +16, ±1 dB dBm
Output Level Range: 0 to -15 dB
Stereo L-R Separation: 80 dB
Signal-to-Noise Ratio: 85 dB
Harmonic Distortion: <0.3 % THD
Impedance: 600 Ohm

General

Power Requirements Voltage: 90 to 140 VAC Frequency: 57 to 63 Hz

Power: 40 W

LNB Supply: 19 to 21 VDC 480 mA, maximum

Mechanical

Material: Steel Chassis

Dimensions: 48 W x 46 D x 4.24 H cm

Weight: 5.0 kg

Connectors (Rear Panel)

RF Input/LNB Power: "F" type, female Aux Video Input/Output: Screw Terminal Left Audio Input/Output: Screw Terminal Right Audio Input/Output: Screw Terminal Mono Audio Input/Output: Screw Terminal

Cue Tone Output: Screw Terminal Asynchronous Data: Screw Terminal High Speed Data: Screw Terminal

Ground: Screw Terminal
TvPassTM Security Slot: Card Slot

Controls (Front Panel)

Keypad: Push Buttons

Refer to product instruction manual for additional specification measurements and notes.

Ordering Information

Model Stock No. Description

CDSR-4400X 6195X Commercial Digital Satellite Receiver DigiCipher II & MPEG II





Toll Free: 800-423-2594 www.multicominc.com multicom@multicominc.com