

MIBT/SIBT M3T-25 MIBR/SIBR M3T-25

Retro Linx

Fiber Optic VSB/AM Transmitters/Receivers - 5 Channels



MIBT/MIBR
Sample Rack Mount



SIBT/SIBR
Sample Stand Alone

○ Features & Benefits

- Low Cost
- 5-250 MHz RF bandwidth
- SIBT/SIBR Designed for Stand Alone Applications
- MIBT/MIBR fits in our MIRC-12 and FIRC-3 Rack Chassis' for 19 Inch Rack Mounting
- Up to Five Channels Over a Multimode Fiber
- Distance to 3 km

○ Specifications

LINK @ 25 °C, Single-mode Fiber

Bandwidth: 5-250 MHz
 Operating Wavelength: 1310 nm
 CATV Channels: 5
 CNR (-7 dBm Input, 5 Ch. Load): 47 dB
 CSO (5 Ch. Load): -71 dB
 CTB (5 Ch. Load): -55 dB
 Input/Output Impedance: 75 Ohms
 Operating Temperature Range: +10 to +40 °C
 Weight: 6 oz, 170 g (per unit)

Physical Dimensions

SIBT (WxHxL): 3.75 x 2.95 x 1.12 in
 146 x 74 x 28 mm
 MIBT (WxHxL): 1.15 x 3.5 x 7.5 in
 29 x 89 x 191 mm

Transmitters

RF Input Level (5 Channel): +6.0 dBmV
 Optical Output: -7 dBm
 Power Supply Voltage:
 MIBT: 12 VDC
 SIBT: 9 VDC
 Power Dissipation: 1.8 W

Receiver

Optical Input Range: -16 to -6 dBm
 Power Supply Voltage: -12 VDC
 Power Dissipation: 1.8 W

Connectors

Optical Output: ST™
 RF Input: "F"
 Power Supply
 SIBT: ACCS-PS-90 (BT Stock No. 7417)
 SIBR: ACCS-PS-120 (BT Stock No. 7419)
 MIBT/MIBR:
 MIPS-12C (BT Stock No. 7722C)
 Power Supply and
 MIRC-12V (BT Stock No. 7715)
 Chassis

The MIBT/SIBT-M3T-25 series fiber optic transmitters along with the MIBR/SIBR-M3T-25 receivers provide a high-quality system for transporting up to five TV channels over a multimode optical fiber. With an RF bandwidth from 5 MHz to 250 MHz, these units can transmit sub-band, low-band, FM, mid-band or high-band channels. Optimum performance is achieved when the channel (frequency) plan is within a single octave of bandwidth. The system can transmit signals from a VCR, camcorder or cable television feed over a distance of 3 km on one multimode fiber. Tri-color LED's are used to indicate optimum RF input level on the transmitters and optical input status on the receivers. Green indicates an acceptable level, red is too high and amber is too low. These products are recommended for use with multimode fibers only and require a minimum fiber bandwidth of 250 MHz.

○ Ordering Information

Model	Stock No.	Description
SIBT-M3T-25	7422 S	Fiber Optic Transmitter, 5 Channel 5-250 MHz, Multimode, 1310 nm, ST Connector, -7 dBm Optical
SIBR-M3T-25	7432 S	Fiber Optic Receiver, 5 Channel 5-250 MHz, Multimode, 1310 nm, ST Connector
MIBT-M3T-25	7422	Fiber Optic Transmitter, 5 Channel 5-250 MHz, Multimode, 1310 nm, ST Connector, -7 dBm Output
MIBR-M3T-25	7432	Fiber Optic Receiver, 5 Channel 5-250 MHz, Multimode, 1310 nm, ST Connector

Order From: 

Toll Free: 800-423-2594
 www.multicominc.com
 multicom@multicominc.com