# **MWT Series**

## **Tunable Notch Traps**



### MWT-U

#### O Features & Benefits

- Low Insertion Loss
- VHF and UHF Tunable Notch Traps
- Ideal for Eliminating Interference from Off-Air Antennas
- Rugged Die-Cast Housing with Mast and Flat Surface Mount Ability

The MWT Series are professional quality, O Specifications tunable notch traps. These units are designed to trap a very narrow band of R frequencies while passing the rest of the band with very low insertion loss. Two tunable traps are employed which can be tuned to the same frequency to provide up to 60 dB of attenuation. The MWT Series can be used in conjunction with an off-air antenna feed to eliminate interference (i.e. adjacent channels). The MWT Series features a rugged die cast housing and can be mast or flat surface mounted.

RF	MWT-2b	MWT-3b	MWT-4	MWT-U
Frequency Range MHz Trap Tuning: Bandpass:	54-108 54-216	174-216 54-216	108-174 54-300	470-890 54-890
Insertion Loss (Max) - Outside Notch 54-108 MHz: 108-174 MHz: 174-216 MHz: 470-890 MHz:	dB 1.0 1.0 1.0 NA	1.0 1.0 1.0 NA	1.0 1.0 1.0 NA	1.5 1.5 1.5 0.5
Notch Depth - Maximum dB:	60	60	60	60
Notch Depth Range dB:	0.5-40	0.5-40	0.5-40	NA
Notch Width dB vs. Freq.:	-3 (1.9 MHz) -30 (120 kHz) -40 (45 kHz) -30 (400 kHz)	-3 (2.0 MHz) -30 (100 kHz) -40 (35 kHz) -40 (100 kHz)	-3 (2.0 MHz) -30 (100 kHz) -40 (35 kHz)	-3 (10 MHz) -12 (3 MHz) -20 (1.8 MHz)
Impedance - All Ports ohm:	`75	`75	75	75
Return Loss - Input & Output dB 54-108 MHz: 108-174 MHz: 174-216 MHz: 470-890 MHz:	20 20 20 NA	20 20 20 NA	20 20 20 NA	10 10 10 15
General				
Power Passing Ability: Voltage VAC: Frequency Hz: Current A:	NO NA NA NA	NO NA NA NA	NO NA NA NA	YES 100 0-60 6
Controls (Front Panel)				
Trap Coarse & Fine Tune: Trap Depth:	Controls Control	Controls Control	Controls Control	Controls NA

#### Mechanical

Dimensions (LxWxD): 6.38 x 2.75 x 3.25 in

(162 x 70 x 83) mm

Weight: 1.5 lbs, (0.68 kg) **Connectors (Front Panel)** 

RF Input & Output: "F" Type Female

#### O Ordering Information

Model	Stock No.	Description
MWT-2b	4505	Tunable Notch Trap 54-108 MHz
MWT-3b	4529	Tunable Notch Trap 174-216 MHz
MWT-4	4898	Tunable Notch Trap 108-174 MHz
MWT-U	4614	Tunable Notch Trap 470-890 MHz

Available through Multicom, Inc. 1076 Florida Central Parkway, Longwood, FL 32750

> Ph: 407-331-7779 Toll Free: 800-423-2594 Fax:407-339-0204 www.multicominc.com