

Solder Back Indoor/Outdoor Splitters

SXRS Series & SCVS Series

○ Features & Benefits

- Superior Performance to 1000 MHz
- 2,3,4, 6 (SCVS Only) and 8 Way Models
- Die Cast Housing
- RFI Shielding 120 dB
- Built-in Ground Block



SXRS-2



SXRS-3



SXRS-4



SXRS-8



SCVS-2



SCVS-3



SCVS-4



SCVS-6



SCVS-8

○ Specifications

Electrical	SCVS/SXRS-2	SCVS/SXRS-3	SCVS/SXRS-4	SCVS-6	SCVS/SXRS-8
Number of Outputs:	2	3	4	6	8
Frequency Range (MHz):	5-1000	5-1000	5-1000	5-1000	5-1000
Splitter Loss (dB) (max)					
5-500 MHz:	3.6	5.8	7.0	9.5	10.5
500-860 MHz:	3.8	6.2	7.5	10.0	11.5
860-1000MHz:	4.2	6.8	8.0	11.0	12.0
Input Return Loss (dB) (min):					
5-40	16	16	16	16	16
40-500 MHz	22	20	20	18	20
500-860 MHz	20	20	18	18	20
860-1000 MHz	18	16	16	18	16
Isolation Between Outputs (dB) (min):					
5-40	22	22	22	25	22
40-500 MHz	30	25	25	28	25
500-860 MHz	26	25	25	25	25
860-1000 MHz	24	21	22	22	21

○ Ordering Information

Model	Stock No.	Description
SCVS-2		Splitter, 2 Way Solder Back, 5-1000 MHz, L Style
SCVS-3		Splitter, 3 Way Solder Back, 5-1000 MHz, L Style
SCVS-4		Splitter, 4 Way Solder Back, 5-1000 MHz, L Style
SCVS-6		Splitter, 6 Way Solder Back, 5-1000 MHz, L Style

Model	Stock No.	Description
SCVS-8		Splitter, 8 Way Solder Back, 5-1000 MHz, L Style
SXRS-2		Splitter, 2 Way Solder Back, 5-1000 MHz, In-Line Style
SXRS-3		Splitter, 3 Way Solder Back, 5-1000 MHz, In-Line Style
SXRS-4		Splitter, 4 Way Solder Back, 5-1000 MHz, In-Line Style
SXRS-8		Splitter, 8 Way Solder Back, 5-1000 MHz, L Style

Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com