

# PS Series

## Preamplifier Power Supplies



PS-1526



PS-1536

### ○ Features & Benefits

- Single Output, 40mA Capacity
- Regulated and Surge Protected
- Auxiliary AC Receptacle

The PS-1526 and PS-1536 are professional quality, DC power supplies designed to power SCMA and CMA Series antenna preamplifiers. Both units provide -21 VDC and allow for a combined VHF and UHF feed to be diplexed with the power feed. The PS-1536 has a dual output for powering two loads, with a maximum current rating of 100 mA. The PS-1526 has a single output for powering one load, with a maximum current rating of 40 mA.

The PS-1526 and PS-1536 are housed in an aluminum case with an auxiliary AC receptacle. Both units offer regulated and surge-protected power. The PS-1536 has a panel mounted fuse, provides an additional level of short circuit protection on the regulator and a clamped output voltage to protect connected loads.

### ○ Specifications

#### PS-1536

##### RF

Thru-Line Insertion Loss  
VHF (10-300 MHz): 0.2 dB  
UHF (470-806 MHz): 0.2 dB

Thru-Line Return Loss  
VHF (10-300 MHz): 20 dB  
UHF (470-890 MHz): 20 dB

Isolation Between Outputs:  
10-700 MHz: 50 dB  
700-806 MHz: 35 dB

Impedance: 75  $\Omega$

##### Electrical

Output Voltage: -21 VDC  
Current @ 105 VAC Input: 100 ma

##### General

Power Requirements:  
117 VAC,  $\pm 10\%$ ,  
60 Hz, 0.11 A  
Temperature Range: 0 to +50  $^{\circ}\text{C}$

##### Mechanical

Dimensions (WxHxD):  
8.25 x 3.50 x 2.25 in.  
210 x 89 x 57 mm  
Weight: 2.00 lbs, 0.91 kg

##### Connectors

Input: "F" type, female  
Output + DC: "F" type, female

#### PS-1526

##### RF

Thru-Line Insertion Loss  
VHF (10-300 MHz): 0.3 dB  
UHF (470-806 MHz): 0.5 dB

Thru-Line Return Loss  
VHF (10-300 MHz): 26 dB  
UHF (470-890 MHz): 22 dB

Impedance: 75  $\Omega$

##### Electrical

Output Voltage: -21 VDC  
Current @ 105 VAC Input: 40 ma

##### General

Power Requirements:  
117 VAC,  $\pm 10\%$ ,  
60 Hz, 0.07 A  
Temperature Range: 0 to +50  $^{\circ}\text{C}$

##### Mechanical

Dimensions (WxHxD):  
4.75 x 3.25 x 2.75 in.  
121 x 83 x 70 mm  
Weight: 1.25 lbs, 0.57 kg

##### Connectors

Input: "F" type, female  
Output + DC: "F" type, female

### ○ Ordering Information

Model	Stock No.	Description
PS-1526	1526	Power Supply Single Output, -21VDC @ 40mA
PS-1536	1536	Power Supply Dual Output, -21VDC @ 100mA

Order From:



Toll Free: 800-423-2594  
www.multicominc.com  
multicom@multicominc.com