



PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive
Waukegan, IL 60085

PART NUMBER: 92008
DESCRIPTION: RG-6/U GAS INJECTED COAXIAL CABLE WITH ALUMINUM BRAID – 3.0 GHZ SWEEP TESTED
RATING: ETL DUAL LISTED AS CM/CL2 AND CATV

Construction Parameters:


		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	18 AWG (1/.040) Copper Clad Steel		0.040
Dielectric:	Foam Polyethylene color natural	0.070	0.180
Shielding:	Polyester/Aluminum Fusible Tape plus Aluminum Braid		0.216
Jacket:	PVC	0.032	0.269

Electrical Properties:

	<u>VALUE*</u>
Impedance (ohms):	75
Capacitance (pF/ft):	17
Velocity of Propagation (%):	81
Attenuation (db/100 ft):	
10 MHz	0.8
50 MHz	1.4
100 MHz	1.9
200 MHz	2.9
400 MHz	3.9
700 MHz	5.4
1000 MHz	6.6
1200 MHz	8.9
1450 MHz	10.1
1800 MHz	10.9
2000 MHz	11.3
2500 MHz	12.2
3000 MHz	13.5

Cable Cross-section:

(NOT TO SCALE)



Miscellaneous Information:

Package: 1000' coil – printed box
 Jacket Color: Black
 Jacket Print: COLEMAN CABLE 92008 RG6 18 AWG CCS DUAL SHIELD (ETL) 3020454
 (Sequentially footprinted) CM OR CL2 OR CATV 75C SUN RES SWEPT TO 3.0 GHZ
 Applicable NEC Article: 725 and 820
 Flame Rating: UL-1581 Vertical Tray Flame Test
 Max. Temperature Rating: 75° C
 Approximate Weight (lb/1000 ft): 30

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

Company Name: _____

Customer Approval: _____

Date: _____

09/20/2006

* =Nominal value
By: PEM

Order From:  800-423-2594
www.multicominc.com
multicom@multicominc.com