

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085

PART NUMBER: 92042

RG-6 QUAD SHIELDED COAXIAL CABLE WITH TWO **DESCRIPTION:**

FOILS PLUS TWO ALUMINUM BRAIDS

ETL DUAL LISTED AS CM/CL2 and CATV RATING:

Construction Parameters:


| | | Wall (in)* | OD (in)* |
|------------------|---|------------|----------|
| Conductors: | 18 AWG (1/.040) Copper Clad Steel | | 0.040 |
| Dielectric: | Foam Polyethylene color natural | 0.070 | 0.180 |
| Shielding 1 & 2: | 100% Bonded Polyester/Aluminum Tape plus Aluminum Braid | | |
| | | | 0.216 |
| Shielding 3 & 4: | 100% Polyester/Aluminum Tape plus Aluminum Braid | | 0.249 |
| Jacket: | PVC | 0.029 | 0.295 |

Electrical Properties:

Cable Cross-section:

(NOT TO SCALE)

| | | VALUE* |
|----------------------------|----------|---------------|
| Impedance (ohms): | 75 | |
| Capacitance (pF/ft): | 17 | |
| Velocity of Propagation (9 | 81 | |
| Attenuation (db/100 ft): | 10 MHz | 8.0 |
| , | 50 MHz | 1.0 |
| | 100 MHz | 1.3 |
| | 200 MHz | 2.0 |
| | 400 MHz | 3.0 |
| | 700 MHz | 5.9 |
| | 1000 MHz | 7.6 |
| | 1500 MHz | 10.3 |
| | 1450 MHz | 10.1 |
| | 2000 MHz | 11.3 |
| | 2500 MHz | 12.2 |
| | 3000 MHz | 13.5 |
| | | |



Miscellaneous Information:

Package: 1000 foot coil in printed box

Jacket Color: Black

COLEMAN CABLE 92042 RG6 18 AWG CCS QUAD SHIELD (ETL) 3020454 CM OR Jacket Print (White):

CL2 OR CATV 75C SUN RES SWEPT TO 3.0 GHZ (Sequentially footprinted)

Applicable NEC Article: 725, 800 & 820

Flame Rating: **UL-1581 Vertical Tray Flame Test**

75° C Maximum Operating Temperature: Approximate Weight (lb/1000 ft): 33

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and \pm 10% of total order requested.


Order From: **MULTICOM**

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

| Company Name: | | |
|--------------------|-------|--|
| Customer Approval: | Date: | |
| | | |

09/20/06

Issued:



* = Nominal value By: HCS