

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085

PART NUMBER: 921007-

DESCRIPTION: RG-6/U PLENUM COAXIAL CABLE WITH FOIL AND 90%

ALUMINUM BRAID

RATING: ETL DUAL LISTED AS CMP/CL2P/CATVP

C(ETL) CERTIFIED AS CMP FT6

APPLICATIONS: CATV

Construction Parameters:

| | | <u>Wall (in)*</u> | OD (in)* |
|-------------|--|-------------------|----------|
| Conductors: | 18 AWG (1/.040) Solid Bare Copper | | 0.040 |
| Dielectric: | Foam FEP color natural | 0.065 | 0.170 |
| Shielding: | Aluminum/Polyester/Aluminum Foil with 90% Aluminum Braid | | 0.200 |
| Jacket: | Low Smoke PVC | 0.022 | 0.243 |

Electrical Properties:

Cable Cross-section:

(NOT TO SCALE)

| | | VALUE* |
|---------------------------|----------|--------|
| Conductor Resistance (o | 6.5 | |
| Impedance (ohms): | 75 | |
| Capacitance (pF/ft): | 16.5 | |
| Velocity of Propagation (| 82 | |
| Attenuation (db/100 ft): | 50 MHz | 1.5 |
| | 100 MHz | 1.9 |
| | 200 MHz | 3.2 |
| | 550 MHz | 5.3 |
| | 750 MHz | 6.1 |
| | 950 MHz | 6.8 |
| | 1450 MHz | 9.3 |
| | 1750 MHz | 10.5 |
| | 2150 MHz | 12.0 |
| | 2200 MHz | 12.5 |
| | 3000 MHz | 14.5 |



Miscellaneous Information:

Jacket Color: Natural

Jacket Print: (Teal/Aqua): COLEMAN CABLE 921007 RG6 18 AWG BC DUAL SHIELD 90% AL ASCENDING/DESCENDING FOOTAGE BRAID C(ETL)US 3020464 CMP OR CL2P FT6 75C SWEPT TO 3.0

MARKING GHZ
Applicable NEC Article: 725 8

725 & 800 UL 910 Steiner Tunnel Smoke and Flame Test

Flame Rating: UL 9 Approximate Weight (lb/1000 ft): 42

This product complies with European Directive 2002/95/EC (RoHS) On special orders the customer will accept all factory lengths and \pm 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

| Company Name: | | |
|--------------------|-------|--|
| Customer Approval: | Date: | |
| | | |

Issued: 09/20/06

Order From: MULTICOM

800-423-2594 * = Nomin www.multicominc.com

multicom@multicominc.com

* = Nominal value By: RBC