

## **PRODUCT DATA SHEET**

1530 Shields Drive Waukegan, IL 60085

# Coleman Cable, Inc.

**PART NUMBER:** 99901-

RG 11/U PLENUM COAXIAL CABLE 65% TINNED COPPER **DESCRIPTION:** 

**BRAID** 

**RATING: UL LISTED AS CL2P/CATVP** 

CSA LISTED AS CMP FT6

#### Construction Parameters:

		Wall (in)*	OD (in)*
Conductors:	14 AWG (1/.064) Solid Bare Copper		0.064
Dielectric:	Foam FEP color natural	0.108	0.280
Shielding:	Aluminum/Polyester/Aluminum Shield and 65% Tinned Copper Braid		0.305
Jacket:	PVDF (Kynar <sup>?</sup> )	0.017	0.339

## **Electrical Properties:**

		VALUE*
Conductor Resistance (ohms	2.5	
Impedance (ohms):		75
Capacitance (pF/ft):		16.5
Velocity of Propagation (%):		82
Attenuation (Max db/100 ft):	50 MHz	1.2
	100 MHz	1.7
	200 MHz	2.2
	400 MHz	3.3
	700 MHz	4.5
	900 MHz	5.2
	1000 MHz	5.5
	2000 MHz	10.0
	2200 MHz	10.4

## Cable Cross-section:



#### Miscellaneous Information:

Issued:

Jacket Color: Natural

COLEMAN CABLE 99901 E100316-I 14 AWG RG 11/U TYPE Jacket Print (Blue):

CL2P/CATVP (UL) 125 C LL53149 CSA CMP FT6 WO# Sequential Footage Marking

Applicable NEC Article: 725, 820

Flame Rating: UL 910 Steiner Tunnel Smoke and Flame Test, CSA FT6

Cable Temperature Rating: 125° C Approximate Weight (lb/1000 ft): 62

On special orders the customer will accept all factory lengths and  $\pm$  10% of total order requested. The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.

Company Name:		
Customer Approval:	Date:	
04/26/06		* = Nominal value

Order From: **MULTICOM** 



**RBC** 

By: