



DZS provides a full line of powerful Layer 2 and Layer 3 business class Ethernet Switching solutions. Our portfolio of switches provides premium features and functionality at an affordable price. Our products are easy to deploy and reliable while providing high-bandwidth switching, filtering, and traffic management without delaying data. Whether you're in need of a new switch or upgrading an old one, DZS can meet your needs.

DZS MODEL	V2224-CU	V2224-OP	V5624G	V5648G	V6824XG	V6848XG	M2400
Product Picture							
Product Description	24 RJ45 GIG PORTS	24 SFP GIG PORTS	COMBO RJ45 & SFP	48 RJ45 GIG PORTS	24 SFP+ 1G/10 PORT	48 SFP+ 1G/10 PORT	IPMPLS MOBIL BACKHAUL ROUTER
WEB SMART							
L2	X	X		X	X	X	X
L3			X	X	X	X	X
L3 FEARTURES							
IP-MPLS							X
G.8032							X
VPLS							X
Port Configuration							
10/100/1000Base-T ports (RJ45)	24		24	48			
10/100/1000Base-SFP PORTS		24	24			48	
100M/1G/10G SFP+ Ports					24		4
4-port 40GE (QSFP+) / 100GE (QSFP28)							
24-port 10GE (SFP+) / 25GE (SFP28)							
Uplink Ports Fixed							
RJ45							
SFP							
SFP+			4	4	4		
Uplink modules							
FE/GE	X	X					
RJ45							X
SFP GIG							X
10G SFP+	X	X	X	X	X		X
CWDM: 2 x 8 channel CWDM							X
XG-PON1							
GBs Switching Capacity	88	88	168	216	480	960	200
IEEE 1588v2 TC							X
POWER							
AC	X	X	X	X	X	X	X
DC	X	X	X	X	X	X	X
TEMPATURES							
Operating Temperature	-4~148°F (-20~65°C)	-4~148°F (-20~65°C)	-4~140° F (-20 ~ 60°C)	-4~140° F (-20 ~ 60°C)	0°C ~ 50°C	32~122°F (0~50°C)	-40~65°C
Storage Temperature	-40~158°F (-40~70°C)	-40~158°F (-40~70°C)	-40~176° F (-40 ~ 80°C)	-40~176° F (-40 ~ 80°C)	-40°C ~ 70°C	-40~158°F (-40~70°C)	
PRODUCT WEBLINK	CLICK HERE	CLICK HERE	CLICK HERE	CLICK HERE	CLICK HERE	CLICK HERE	CLICK HERE



Partnering to Build Better Networks Today



All products above are available at:
www.multicominc.com
 800-423-2594