



Fixed Fiber Optic Attenuators

The Multicom Singlemode Fixed Fiber Optic Attenuators offer low return loss, high stability, a variety of attenuation values in 1dB increments, and all standard connectors.

Features:

- Fully compatible with LC/SC/FC fiber optic connectors
- Precise attenuation values
- Industry standard attenuation levels
- Low PDL and insertion loss
- Precision polishing for reduced back reflection
- Highly Reliable Physical Contact Connectors
- RoHS compliant



LC Attenuator




SC Attenuator



FC Attenuator

Parameter	Specification
Connector	SC/FC/LC
Connector Gender	Fixed male to female
Transfer Mode	Singlemode 9/125μm
Operating Wavelength	1260 ~ 1620nm (Singlemode)
Attenuation	5dB
Attenuation Accuracy	± 0.5dB
Return Loss	≥ 55dB UPC, ≥60dB APC
Max Optical Input Power	200mW
Polarization Dependent Loss	≤0.2dB
Operating Temperature	-40 ~ 80°C
Storage Temperature	-45 ~ 85°C
Humidity	95% RH
Compliance	Telcordia GR-20-CORE, GR-326 and TIA/EIA 568C, RoHS

FOATT-xx/UPC-xDB



www.multicominc.com

800-423-2594

Multicom, Inc.
 1076 Florida Central Parkway
 Longwood, FL 32750
 Ph: 407-331-7779
 Fax: 407-339-0204
 Email: multicom@multicominc.com