

5222XG



5222XG XGS-PON ONT

The first generation of 10 Gigabit X-Series ONT enables subscribers to enjoy bandwidth-intensive multimedia services with leading-edge XGS-PON technology.

Features & Benefits

- + Supports 10Gbps/10Gbps (Downstream/Upstream) with integrated XGS-PON WAN interface
- + High capacity multi-rate 1G/2.5G/5G/10G Ethernet interface
- + Two gigabit multi-rate 10/100/1000M Ethernet interfaces
- + Two POTS interfaces compliant to SIP and MGPC telephony standards
- + Supports Dynamic Bandwidth Allocation (DBA) mechanism in compliance with ITU-T G.9807

The DZS 5222XG is a high-performance, XGS-PON compliant Optical Network Terminal (ONT) able to support service provider requirements for high-speed data and voice in a cost-effective design. The ONT is fully compliant with ITU-T G.9807.1 XGS-PON standard with integrated, on-board optics supporting 1270nm and 1577nm wavelengths. The 5222XG offers symmetrical data rates of 10Gbps downstream and 10Gbps upstream able to deliver access edge services and full range of residential and business use cases required. With unique DZS's software management features, subscribers can enjoy hyper-connected multimedia services faster, easier, faster and more reliably.

The DZS 5222XG includes one SC/APC XGS-PON interface, one 1/2.5/5/10GBase-T port, two 10/100/1000Base-T ports, and two FXS RJ11 voice ports. The ONT supports wire-speed L2 bridging and carrier grade lifeline voice services using a DZS approved battery backup unit with battery status telemetry.

Advanced XGS-PON ONT

5222XG



Service Scenario

The XGS-PON network consists of an Optical Line Termination (OLT) located at the Central Office, and a set of residential Single-Family Unit (SFU) and Multi Dwelling Unit (MDU) locations with Optical Network Terminals (ONTs). Between them is the optical distribution network (ODN) comprised of fibers, passive optical splitters and couplers.

The 5222XG ONT support 10 Gigabit symmetrical data using the XGS-PON standard. Services include High-Speed Internet (HIS), Packet Voice, IPTV, OTT video, and cloud enabled services to multi-media devices.

Key Service Attributes

- + FSAN ITU-T G.9807.1 XGS-PON compliant
- + One 10GBase-T Ethernet port, RJ45 supporting 10Gbps symmetrical services
- + Two 1GBase-T Ethernet ports, RJ45 supporting 1Gbps symmetrical services
- + Two voice ports, FXS interfaces compliant to ANSI standards, SIP and MGCP
- + MTU jumbo frame 9216-byte support
- + IPTV multicast, IGMPv2 and IGMPv3 services
- + Any-port, Any-service data model
- + Traffic management including Q-in-Q tagging, 802.1Q VLANs, multiple subscriber VLANs, per-port rate limiting
- + 802.1p priority bits, DiffServ and priority queues based on services types.
- + Transparent LAN services, LLDP-MED
- + 12 VDC power adapter, optional uninterruptable service power source with battery backup

Advanced XGS-PON ONT

5222XG



Features, Protocols, Interfaces

System

- + 512MB Flash Memory
- + 1G SDRAM (DDR)
- + XGS-PON WAN Interface
- + Capacity: 10Gbps Down/10Gbps Up

Interfaces

- + WAN: 1 SC/APC port, XGS-PON
- + LAN: 1 port 1/2.5/5/10GBase-T Ethernet (RJ45), 2 ports 10/100/1000MBase-T Ethernet (RJ45)
- + Telephone: 2 ports 2-wire RJ11
- + Power: 1 2-pin barrel connector, optional 1 2x4 8-pin battery connector
- + LED Indicators
- + Power switch
- + Recessed RESET button

XGS-PON

- + N1 Class, 20km (12.4 miles), reach, max split 128
- + Maximum ODN Attenuation, +29 dB link budget
- + Transmitter, 1270nm, +2.0 to +7 dBm
- + Receiver, 1577nm, -28 dBm
- + Forward Error Correction (FEC) per G.989.3

Quality of Service

- + HW-based internal IEEE 802.1p (CoS)
- + Strict Priority (SP)
- + 802.1Q(VLAN tag) QoS mapping ToS/CoS
- + 8 queues per port
- + Classified traffic can be tagged with VLAN ID and Ethernet Priority bit, and can be assigned to priority queues
- + Classify packets into different IEEE 802.1p priority queues according to DSCP values (RFC 2475)
- + The range of traffic shaping or rate-limit shall be between 64 Kbps to the maximum port rate with 64kbps granularity. The accuracy error shall be less than $\pm 10\%$.
- + DSCP IP CoS (RFC 2475)

Telephone

- + SIP (RFC 3261)
- + MGCP
- + RENs per line: 5 maximum
- + Drop length: Residential short loop, 152.4 m (500 ft.)
- + Output max: 25mA
- + Ring voltage: 48Vrms @ 20/25 Hz

Software Features

- + IEEE802.1D and IEEE802.1Q
- + Address learning with auto aging-L2/BPDU Filter
- + Support 2048 MAC learning addresses
- + Multiple T-CONTs/GEM ports per device
- + Flexible mapping between GEM port and T-CONT
- + Priority queues and scheduling on upstream
- + Activation with automatic discovered serial Number and password
- + Dying Gasp

Management

- + ITU-T 984.1/G988 compliant OMCI interface
- + CPE Manager Web UI
- + CLI over telnet
- + SNMP Client
- + TR-069, TR-104, TR-98
- + LED indications for status

Compliance

- + FCC Part 15 Class B
- + ICES-003 Class B
- + EN55022, EN55024
- + IEC 62368-1
- + FDA IEC 60825-1
- + RoHS 2015/863/EU

Physical & Environmental Specifications

Dimensions (W x H x D)	8.5" (216mm) x 5.6" (142mm) x 1.4" (35mm)
Operating temperature (-C and -I)	0~+40°C Commercial
Storage temperature	-4~149°F (-20~65°C)
Operating humidity	5 to 90% (non-condensing)
AC power adaptor	90-240VAC, 50/60Hz
DC power	+12 VDC nominal, +10-16 VDC / 1.5A

Voice lines	2 x FXS (RJ11)
LAN 10GE	1 x 1/2.5/5/10GBase-T (RJ45)
LAN 1GE	2 x 10/100/1000MBase-T (RJ45)
Optical line	1 x SC/APC, XGS-PON
	Power switch, recessed RESET button
Power consumption	Approx. 15W