



Specification Sheet

Lake Cable Part #: AV143CSCAT6

Description: Two element composite cable, unshielded and an overall PVC jacket for low-voltage electronic cable applications

- Category 6 - 23 AWG 4 Pairs Unshielded
- 14 AWG 3C Shielded Cable

Element 1: One Component 23AWG 4 UTP Cat6:

1. Jacket:

- 1.1. Material: Polyvinylchloride
- 1.2. Wall Thickness: **0.020"**
- 1.3. Diameter: **0.230"**
- 1.4. Ripcord: Nylon Required
- 1.5. Color: Blue + Standard-UL Print.

2. Nominal Electrical Characteristics:

- 2.1. Impedance: 100 ± 15Ω (.772 to 100 MHz)
- 2.2. Max. Conductor Resistance: **9.38 Ω/100 Meters @ 20°C**
- 2.3. Max. Resistance Unbalance: 5%
- 2.4. Max. Capacitance Unbalance: 330 pF/100 Meters
- 2.5. Max. Delay Skew: 45 ns/100 Meters
- 2.6. Max. Velocity of Propagation: 68%

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

Typical Transmission Specifications

Freq (MHz)	Ins. Loss (dB/100m)	NEXT Loss (dB)	PSNEXT Loss (dB)	ACR (dB)	PSACR (dB)	ELFEXT (dB)	PSELFEXT (dB)	Return Loss (dB)
1	2.0	82.3	80.3	80.3	78.3	75.8	72.8	20.0
4	3.7	73.3	71.3	67.6	67.6	63.8	60.8	23.0
8	5.2	68.8	66.8	63.6	61.6	57.7	54.7	24.5
10	5.8	67.3	65.3	61.5	59.5	55.8	52.8	25.0
16	7.3	64.2	62.2	56.9	54.9	51.8	48.7	25.0
31.25	10.4	59.9	57.9	49.5	47.5	45.9	42.9	23.6
62.5	14.9	55.4	53.4	40.4	38.4	39.9	36.9	21.5
100	19.2	52.3	50.3	33.1	31.1	35.8	32.8	20.1
155	24.4	49.4	47.4	25.0	23	32.0	29.0	18.8
200	28.1	47.8	45.8	19.7	17.7	29.8	26.8	18.0
250	31.9	46.3	44.3	14.5	12.5	27.8	24.8	17.3
300	35.3	45.1	43.1	9.8	7.8	26.3	23.3	16.8
350	38.6	44.1	42.1	5.5	3.5	24.9	21.9	16.3
400	41.7	43.3	41.3	1.6	-	23.8	20.8	15.9
500	47.5	41.8	39.8	-	-	21.8	18.8	15.2
555	50.5	41.1	39.1	-	-	20.9	17.9	14.9

TIA/EIA-568-b.2-1 Category 6 Compliant
ISO/IEC 11801, 2nd Ed. Class E Compliant

Purchase from Multicom  www.multicominc.com | 800-423-2594



Specification Sheet

Lake Cable Part #: AV143CSCAT6

Element 2: 14 AWG 3C Shielded Cable

1. Conductor
 - 1.1. AWG Size & Stranding: 14 AWG 19 Strands Class C
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 3 Conductors
2. Insulation
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.009"
 - 2.3. Color Code: Black, Red, White
3. Assembly
 - 3.1. Nominal Lay Length: **3.00" LHL (4.00 tw/ft)**
 - 3.2. Shield: Aluminum/Mylar Tape - 100% Coverage
 - 3.3. Drain Wire: 24 AWG 7 Strands Tinned Copper
4. Jacket
 - 4.1. Material: Polyvinylchloride
 - 4.2. Wall Thickness: **0.015"**
 - 4.3. Diameter: 0.229"
 - 4.4. Color: Gray
 - 4.5. Ripcord: Yes
5. Markings
 - 5.1. Type: Cable permanently identified via surface inkjet print
 - 5.2. Legend: LAKE E171202 14AWG 3C SHIELDED 75°C (UL) CL3R SUN RES FT4 "ROHS II"
MADE IN USA
 - 5.3. Footage Markers: N/A
5. Nominal Electrical Characteristics
 - 5.1. Impedance: 35 Ω
 - 5.2. Capacitance: 50 pF/ft
 - 5.3. DC Resistance: 2.63 Ω /Mft @ 20°C Maximum

Overall Assembly

6. Assembly (Element 1 & 2)
 - 6.1. Cable Lay Length: Pulled in parallel at jacketing
7. Jacket
 - 7.1. Material: Polyvinylchloride
 - 7.2. Wall Thickness: 0.030"
 - 7.3. Diameter: 0.290" x 0.520" \pm .015"
 - 7.4. Color: Black
 - 7.5. Ripcord: N/A
 - 7.6. Weight: 100 Lbs/Mft

Purchase from Multicom  www.multicominc.com | 800-423-2594



Specification Sheet

Lake Cable Part #: AV143CSCAT6

- 8. Markings
 - 8.1. Type: Cable permanently identified via surface inkjet print
 - 8.2. Legend: LAKE CABLE AV143CSCAT6 E171202 14AWG 3C SHIELDED + 23AWG 4PR CAT6 75°C (UL) CL3R SUN RES FT-4 "ROHS II" MADE IN USA
 - 8.3. Footage Markers: Yes
- 9. Standards
 - 9.1. UL listed CL3R per standard 13
 - 9.2. All materials used in the manufacturing of this cable are RoHS II & REACH compliant
 - 9.3. Maximum Operating Voltage: 300V RMS
 - 9.4. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION



Purchase from Multicom  www.multicominc.com | 800-423-2594