



1550nm 10dB Intelligent Direct Modulated Optical Transmitter

Key Features

- » High linearity, optically isolated, distributed AM feedback DFB laser with an optical output power of 10dBm
- » Transmits NTSC, PAL, ATSC, and related digital information for CATV and/or telephony applications
- » 47-1003 MHz RF input bandwidth
- » Front panel RF test point
- » Microprocessor-controlled diagnostics, front panel LCD display and controls
- » Automatic Gain Control (AGC) and Manual Gain Control (MGC) override
- » Integrated SNMP network interface
- » Dual hot-pluggable redundant power supplies



Description

The MUL-1550TX-V-1-10 intelligent directly modulated optical transmitter is mainly used in 1550nm optical fiber transmission systems. It uses a DFB laser with an optical output power of 10dBm, and advanced intelligent electronic predistortion compensation technology (adjustable up to 50km in 1km steps).

This intelligent directly modulated optical transmitter is one of the most important components to build a CATV-HFC network. It is mainly used to transmit analog video, digital television signal, telephone voice signal and data (or compressed data) signal. This Multicom product provides a high quality low cost transmitter solution for a 1550nm optical fiber CATV system.

P/N	Output Power
MUL-1550TX-V-1-10	10 dBm

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204

Email: multicom@multicominc.com



1550nm 10dB Intelligent Direct Modulated Optical Transmitter

Product Specifications

Description

The MUL-1550TX-V-1-10 intelligent directly modulated optical transmitter is mainly used in 1550nm optical fiber transmission systems. It uses a DFB laser with an optical output power of 10dBm, and advanced intelligent electronic predistortion compensation technology (adjustable up to 50km in 1km steps).

This intelligent directly modulated optical transmitter is one of the most important components to build a CATV-HFC network. It is mainly used to transmit analog video, digital television signal, telephone voice signal and data (or compressed data) signal. This Multicom product provides a high quality low cost transmitter solution for a 1550nm optical fiber CATV system.

Technical Specifications

Item	Unit	Technical Parameters
Optical output power	dBm	10
Optical wavelength	nm	1550 ± 10
Dispersion compensation distance	Km	≤ 50
Laser type		ORTEL DFB laser
Optical modulation mode		Direct optical intensity modulation
Optical connector type		SC/APC
Frequency range	MHz	47-862 / 1003 (depending on selected channel load)
RF input level	dBμV	75 - 85 (+15 to +25dBmV)
Flatness in band	dB	± 0.75
RF input impedance	Ω	75
Input return loss	dB	≥ 16
AGC control range	dB	± 5
MGC control range	dB	0 - 2 0
Power supply voltage	V	AC 110V - 250V (50/60Hz) (redundant power)
Consumption	W	30
Operating temperature	°C	0 - +45 (+32 - +113°F)
Storage temperature	°C	-20 - +65 (-4 - +150°F)
Relative humidity	%	Max 95% no condensation
Dimensions	mm	483 (W) x 380 (D) x 44 (H); (19in W x 15in D x 1.75in H)

P/N	Output Power
MUL-1550TX-V-1-10	10 dBm

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204

Email: multicom@multicominc.com