



High Precision Fiber Optic Cleaver

Features:

- Compact body and high precision design
- Applicable for single fiber
- For use on Singlemode and Multi-mode fiber
- 36,000 fiber cleaves life (1,000 fibers x 3 heights x 12 positions)
- Includes soft carrying case and fiber guide tool

The Multicom MUL-FCLEAV-100 is ideal for single fiber FTTx applications. The 16-position blade yields 36,000 single-fiber cleaves before requiring replacement. This easy-to-use precision cleaver provides reliable, repeatable results.



Parameter	Specification
Fiber count	Single fiber
Cleaving length	10-16mm
Fiber holder	Universal, interchangeable
Applicable fibers	Singlemode, Multi-mode
Bare fiber diameter	125 μ m (250-900nm coating)
Cleaving angle (typical)	0.5° with single fiber
Blade life	36,000 fiber cleaves (1,000 fibers x 3 heights x 12 positions)
Blade positions	3 heights, 16 rotating positions
Dimensions (mm)	63W x 76D x 63H
Weight	380g

MUL-FCLEAV-100

www.multicominc.com

Multicom, Inc.
1076 Florida Central Parkway
Longwood, FL 32750
Ph: 800-423-2594 / 407-331-7779
Fax: 407-339-0204
Email: multicom@multicominc.com