



HD Digital Encoder

Product Specifications



Description

The Multicom MUL-HDENC-C-100 High Definition Digital Encoder is compact and economical. This HD Encoder is perfect for multi-video distribution solutions in the commercial and institutional market (hotels, motels, sports bars, restaurants, hospitals, casinos, business and university campuses, digital signage, etc.), as well as home entertainment systems.

The MUL-HDENC-C-100 features a front-mounted LCD display and web-based graphical user interface allowing easy configuration and adjustments.

Features

- HDMI input (unencrypted), RF QAM coax output
- User selectable output: Ch 2 – 135
- Video output selectable 480/720/1080
- Front panel LCD for easy setup
- Web-based graphical user interface
- High quality video and audio on high motion video, sports, text crawls/rolls, etc.
- Cool silent operation

Inputs	
HDMI	1.4v
Audio Inputs	
Audio Input	PCM
Video Encoder	
Video Codecs	MPEG-2 VBR
Video Resolutions	1080p,1080i, 720p, 480p, 480i
Audio Encoder	
Audio Compression	MPEG-1 Layer II, MPEG-4 AAC
RF QAM Support	
Frequency	QAM J.83B: 57-861 MHz (CH 2-CH 135) ATSC: 57- 803 MHz (CH2 - CH 69)
RF Channel Output (Programs / QAM)	1 Program / 1 QAM
Constellation	J.83B: 64 QAM / 256 QAM (STC/HRC/IRC) ATSC: 8VSB
Bandwidth	6 MHz
RF Level Output	+38dBmV Typical
MER	>37dB (38 dB Typical)
Interleaver	Supported (12 presets)
Channel Type	STD, HRC, IRC / ATSC
VCN	VCN Auto, VCN Manual, VCN 1-Part
Attenuation	0 – 20dB (adjustable)
RF Output	"F"- Female 75Ω
Management / Control	
GUI Supported	FireFox, Chrome, Safari, EDGE
GUI Control	RJ-45 10/100
Password Protected	Front Panel, Web Interface
General	
Dimensions	7.5" x 5.25" x 1.75"
Front Panel	LCD Front Panel Control/Status
Power Supply	12VDC, 1.5Amp

MUL-HDENC-C-100

www.multicominc.com

Multicom, Inc.

Ph: 800-423-2594 / 407-331-7779

Fax: 407-339-0204

Email: multicom@multicominc.com