



RFOG Optical Micro-Node

Key Features

- » The laser control circuit uses advanced circuit design, ensuring reliable and stable operation
- » Provides excellent AGC characteristics - when the input optical power range is within -7 ~ +2dBm, the RF output level remains unchanged
- » Optimized circuit design using the SMT production process optimizes the entire signal path, making the optical signal transmission more stable
- » Professional RF attenuator circuit ensures excellent linear attenuation
- » GaAs amplifier device provides low distortion and high reliability
- » Aluminum die casting for efficient cooling and stable performance



Description

The MUL-MN-V-RFOG optical receiver is bidirectional equipment that was specially developed for HFC broadband networks, accommodates FTTH (Fiber to the Home) network topology, while addressing the issues of CATV bidirectional return channel noise and high reliability network security transmission requirements of modern CATV networks.

MUL-MN-V-RFOG

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204
Email: multicom@multicominc.com



Optical Micro-Node

Product Specifications

Item	Unit	Technical Parameter
Forward Optical Receiver		
Optical Parameters		
Optical Receiving Power	dBm	-7 ~ +2
Suggested Use Range	dBm	-3 ~ +1
Optical Return Loss	dB	> 45
Optical Receiving Wavelength	nm	1260 ~ 1620
Optical Connector Type		SC/APC
Fiber Type		Single Mode
Link Performance		
C/N	dB	≥ 51 received optical power (-1dBm)
C/CTB	dB	≥ 63
C/CSO	dB	≥ 60
RF Parameters		
Frequency Range	MHz	54 ~ 1000
Flatness in Band	dB	± 0.75
Rated Output Level	dB μ V	≥ 92 (≥ +32dBmV)
Max Output Level	dB μ V	≥ 92 (≥ +32dBmV)
Output Return Loss	dB	≥ 16
Output Impedance	Ω	75
Return Optical Transmitter		
Optical Parameters		
Optical Transmit Wavelength	nm	1310 ± 10
Laser Type		FP laser
Optical Output Power	mW	1 ± 0.5
Optical Connector Type		SC/APC
RF Parameters		
Frequency Range	MHz	5 ~ 42
Flatness in Band	dB	± 0.75
Input Level	dB μ V	75 ~ 85 (+15 ~ +25dBmV)
Input Return Loss	dB	≥ 16
Output Impedance	Ω	75
NPR Dynamic Range	dB	≥ 10 (NPR ≥ 30 dB) Using the FP laser
General Statistics		
Power Voltage	V	+12VDC (from the included AC Adapter)
Operating Temperature	°C	-30 ~ +70 (-22 ~ +158°F)
Storage Temperature	°C	-30 ~ +70 (-22 ~ +158°F)
Relative Humidity	%	Max 95% no condensation
Consumption	W	≤ 6
Dimensions	mm	154 (L) x 116(W) x 26(H) (6in x 4.6in x 1in)

MUL-MN-V-TR

www.multicominc.com

Specifications subject to change without notice

Multicom, Inc.
 Ph: 800-423-2594 / 407-331-7779
 Fax: 407-339-0204
 Email: multicom@multicominc.com

© 2016 Multicom, Inc.