



OTDR Launch Cable Box

Product Specifications

Description

The Multicom MUL-OTDR-LCB-150M OTDR Launch Cable Box, connects the OTDR to the link-under-test, discloses the insertion loss and reflectance of the near-end connection. The Launch Box creates the proper conditions for testing another similar optical fiber for faults. This method avoids undesirable variations in loss and distance measurements. A launch fiber helps to overcome the blind spot or 'Dead Zone' of an OTDR brought about by high launch power or faults near the launch end of the fiber.



Features

- Ruggedized Case
- Singlemode
- 150 Meters
- SC/UPC to SC/UPC Connectors
- Robust carabiner clip
- Built-in cable management
- Auto-purge valve
- Compound latch with locking feature

Specifications	Parameter
Fiber Type	9/125 Singlemode G652D fiber
Length	150 Meters
Connector 1	Simplex SC/UPC with dust cap
Connector 2	Simplex SC/UPC with dust cap
Typical Loss	< 0.5dB@1310nm for 1000 Meters
Material	SR Polypropylene
Operating Temperature	-40 ~ +55° C (-40 ~ 131°F)
Dimensions	238 x 141 x 66mm (9.3" x 5.5" x 3")



MUL-OTDR-LCB-150M

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594 / 407-331-7779
Fax: 407-339-0204
Email: multicom@multicominc.com