CONFIGURED A/V ENCLOSURES

Choose a configured A/V enclosure to simplify ordering and save time. Ships complete with the accessories most commonly used in A/V installations.

- \checkmark Select an MRK for multi-bay installations, or when open sides are preferable
- ✓ Select an ERK for single bay installations
- See pgs. 20 21 (MRK Series) or pgs. 26 27 (ERK Series) for additional enclosure information and options

Each enclosure is configured for Active thermal management and ships complete with:

Thermal Management

- ✓ Integrated fan top, (MRK features proportional speed fan control)
- ✓ Rear door bottom vent
- ✓ Vent blockers (ERK only)

Cable Management

- ✓ Vertical lacer strip 3 ¼″ width (LACE-OP Series)
- ✓ Horizontal lacer bars, four 'L' shaped straight and two 4" offset
- ✓ Velcro[®] cable management straps, 8" length, 12 qty

Power Distribution

- ✓ 1 qty 20 Amp, 20 outlet power strip with cord, 44 space enclosures (PDT-2020C-NS)
- ✓ 2 qty 10 Amp, 10 outlet power strip with cord, 35 and 40 space enclosures (PDT-1020C-NS)

Accessories

- ✓ Solid front and configurable rear door, locking
- ✓ 10-32 threaded rackscrews, 100 qty
- ✓ Leveling feet, 4 qty
- ✓ Side panels (MRK models with sides only)
- ✓ Ganging hardware (MRK open side models only)

