



IMSA 50-2 Loop Lead-In Cable

Product Specifications

Specifications		Put-Ups
Conductor - Stranded Tinned Copper per ASTM B-8, B-33 Insulation - 18 AWG - .030" PE 16 AWG - .030" PE 14 AWG - .030" PE 12 AWG - .030" PE	Shielding - Aluminum Jacket - Polyethylene Voltage Rating - 600 V Temp. Rating - 75°C	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>



AWG	NO. OF PAIRS	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
18 AWG						
18	1	.030	.762	.286	7.26	29
18	2	.030	.762	.322	8.19	54
18	3	.030	.762	.465	11.81	78
16 AWG						
16	1	.030	.762	.292	7.42	38
14 AWG						
14	1	.030	.762	.332	8.43	55
14	2	.030	.762	.400	10.16	102
14	3	.030	.762	.566	14.38	120
14	4	.030	.762	.584	14.83	171
12 AWG						
12	1	.030	.762	.356	9.04	75

www.multicominc.com

Multicom, Inc.
 Ph: 800-423-2594
 Fax: 407-339-0204
 Email: multicom@multicominc.com