




IMSA 51-1 and 51-3 Loop Detector Cable

Product Specifications

IMSA Specification 51-1 Loop Detector Cable



Specifications		Put-Ups	
Conductor - Stranded Bare Copper per ASTM B-3, B-8	Insulation - PVC/Nylon 14 AWG - .016" PVC + .05" Nylon 12 AWG - .016" PVC + .05" Nylon		Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
Voltage Rating - 600 V Temp. Rating - 75°C			

AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
	INCH	mm	INCH	mm	
14	.026	.660	.115	2.92	16
12	.026	.660	.135	3.43	24

IMSA Specification 51-3 Loop Detector Cable



Specifications		Put-Ups	
Conductor - Stranded Bare Copper per ASTM B-3, B-8	Insulation 14 AWG - .030" XLPE 12 AWG - .030" XLPE		Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
Voltage Rating - 600 V Temp. Rating - 75°C			

AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
	INCH	mm	INCH	mm	
14	.030	.762	.133	3.38	17
12	.030	.762	.150	3.81	26

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204

Email: multicom@multicominc.com