




# IMSA 51-5 and 51-7 Tube Loop Detector Cable

## Product Specifications


### IMSA Specification 51-5 Tube Loop Detector Cable



Specifications		Put-Ups
<b>Conductor</b> - Stranded Bare Copper per ASTM B-3, B-8	<b>Insulation</b> - PVC/Nylon 14 AWG - .015" + .05 Nylon 12 AWG - .015" + .05 Nylon	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
<b>Voltage Rating</b> - 600 V <b>Temp. Rating</b> - 75°C	<b>Jacket- PVC or HDPE</b> 14 AWG - .030" 12 AWG - .030"	

AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
	INCH	mm	INCH	mm	
<b>PVC</b>					
14	.030	.762	.250	6.35	30
12	.030	.762	.250	6.35	36
<b>HDPE</b>					
14	.030	.762	.250	6.35	22
12	.030	.762	.250	6.35	29

### IMSA Specification 51-7 Tube Loop Detector Cable



Specifications		Put-Ups
<b>Conductor</b> - Stranded Bare Copper per ASTM B-3, B-8	<b>Insulation</b> - XLPE 14 AWG - .030" 12 AWG - .030"	Standard Reels 1,000', 2,500', 5,000' <i>Other lengths available. Please consult your factory representative for availability.</i>
<b>Voltage Rating</b> - 600 V <b>Temp. Rating</b> - 75°C	<b>Jacket- PVC or HDPE</b> 14 AWG - .030" 12 AWG - .030"	

AWG	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
	INCH	mm	INCH	mm	
<b>PVC</b>					
14	.030	.762	.191	4.85	31
12	.030	.762	.213	5.33	36
<b>HDPE</b>					
14	.030	.762	.191	4.85	26
12	.030	.762	.213	5.33	31

[www.multicominc.com](http://www.multicominc.com)

Multicom, Inc.  
Ph: 800-423-2594  
Fax: 407-339-0204  
Email: [multicom@multicominc.com](mailto:multicom@multicominc.com)