



# AC Power Adapter

## Key Features

- » Universal Input: 100-240VAC 50/60Hz
- » Highly efficient with low power consumption
- » Short-circuit protection
- » Over-current protection
- » Over-voltage protection
- » Lightweight and compact

Specifications	Description	Notes
<b>Input Characteristics</b>		
AC input voltage	100-240VAC	Variable to 90-264VAC
AC input current	0.65A	
AC frequency	50/60 Hz	Variable to 47/63 Hz
AC Plug type	US	Desk
Power cord rated	2.5A, 250VAC	Removable
Power cord length	1000mm	39 Inches
<b>Output Characteristics</b>		
Voltage	15VDC	
Rated Load	1.5A	
Output power	22W	
Power cord	22 AWG	UL2468
Power cord length	1200mm	48 Inches
Output power plug	4.0 x 1.7 x 10mm barrel	DC power plug
Polarity	Center positive	⊖ ⊕
<b>Environmental</b>		
Operating temperature	0 to 40°C	32 to 104°F
Storage temperature	-10 to 80°C	14 to 176°F
Humidity	25 to 75%	@ 0 to 40°C
Dimensions	88L x 39W x 28H	mm
<b>Compliance</b>	EMI, UL, RoHS, CE	Indoor use only



## Description

The Multicom desktop MCPE15150ADUS provides 15 volts of DC power, up to 1.5 amps, to devices that require low voltage direct current.

**MCPE15150ADUS**

[www.multicominc.com](http://www.multicominc.com)

Multicom, Inc.

Ph: 800-423-2594

Fax: 407-339-0204

Email: [multicom@multicominc.com](mailto:multicom@multicominc.com)