



RG11-60 White Drop Cable

Product Specifications

Key Features

- ◇ Copper covered steel center conductor
- ◇ Gas expanded polyethylene dielectric
- ◇ Swept to 3,500 MHz
- ◇ Color: White
- ◇ Aluminum tape overlap bonded to dielectric
- ◇ Jacket: PVC
- ◇ Braid: 60% aluminum
- ◇ 1,000 foot reels

Specifications

Physical Dimensions	Inches	mm
Nominal Center Conductor Diameter	0.064	1.63
Nominal Diameter Over Dielectric	0.280	7.11
Nominal Diameter Over First Shield (Tape)	0.288	7.32
Nominal Diameter Over Jacket	0.039	10.03
Nominal Jacket Wall Thickness	0.053	1.35
Electrical Characteristics		
Nominal Impedance	75 ohms	
Nominal Velocity of Propagation	84%	

Attenuation (@68° F / 20°C)

Frequency (MHz)	Max (dB/100ft.)	Max (dB/100m)
5	0.38	1.25
55	0.97	3.18
450	2.65	8.69
750	3.44	11.28
1000	4.23	13.87
1750	8.88	29.13
2250	6.50	21.32
3000	7.67	25.16
3500	8.28	27.16

Description

Multicom's RG11 60% AL Braid White Coax Cable is ideal for RF applications including outdoor TV antennas, cable television, and satellite distribution.

M1160-BVW

www.multicominc.com

Multicom, Inc.
Ph: 800-423-2594
Fax: 407-339-0204
Email: multicom@multicominc.com