



FIBER TAP FT-4D

Product Description

Multilink's Fiber Tap FT-4D is designed around adaptability to the ever changing Outside Plant (OSP) infrastructure. Hardened connectors and robust design withstand the harsh OSP world, while allowing flexibility per application. FT-4D's re-entrant design allows for custom field installations of customer input fiber. Predetermined lengths of input fiber can be ordered if required.

Patent in Process

General Specifications

Dimensions:	2.98" H x 4.81" W x 11.41" L
Weight:	1.2 lbs. (without incoming fiber)
Input Ports:	(1) Compression, Ø 0.27"-0.63"
Output Ports:	(4) Multilink Surelight SC simplex or LC duplex
Material:	UV Stabilized Plastic
Mounting:	Integrated Pole and Wall, Aerial, and Pedestal

Ordering Information

<u>Stock ID</u>	<u>Description</u>
Custom	Fiber Tap FT-4D
072-391-10	Tap Bracket Kit - Pedestal or Aerial Mount



Features & Benefits

- O-Ring Sealed design
- Re-Enterable
- Universal Base mounts to Wall or Pole, Aerial, and Pedestal
- Angled Output Adapters, for ease of access to ports
- Multilink Surelight Adapters
- Rugged, Hardened input and output ports
- Up to 4 SC or 8 LC Output connections
- Can be supplied with a length of feeder cable
- Available with pre-installed and tested optical splitter
- Decreased installation and maintenance time, equals savings.



FIBER TAP FT-4D

Ordering Guide

