



FIBER TAP FT-8NC

Product Description

Multilink's Fiber Tap FT-8NC is designed around adapting to the ever changing Outside Plant (OSP) infrastructure. Hardened connectors and rubust design withstand the harsh OSP world, while allowing flexibility per application. FT-8NC's re-enterable design allows for custom field installations of customer input fiber.

FT-8NC has 4 non-captive entry ports.

Patent in Process

General Specifications

Dimensions: 4.37" H x 5.88" W x 16.61" L

> Weight: 3.1 lbs. (without incoming fiber)

Input Ports: (4) Non-Captive Grommets, Ø 0.50 maximum **Output Ports:** (8) Multilink Surelight SC simplex or LC duplex

Splice Tray: Holds (1) 12 Fiber Single Fusion Splice Tray

Material: **UV Stabilized Plastic** Aerial and Pedestal **Mounting:**

Ordering Information

Stock ID **Description**

Fiber Tap FT-8NC Custom

072-391-20 Tap Bracket Kit - Pedestal or Aerial Mount





- O-Ring Sealed design
- Re-Enterable
- · Universal Base mounts to Wall or Pole, Aerial, and Pedestal
- Angled Output Adapters, for ease of access to ports
- Multilink Surelight Adapters
- · Rugged, Hardened input and output ports
- Up to 8 SC or 16 LC Output connections

- 4 Non-Captive Input Ports
- Available with (1) Splice Tray for 24 single fusion splices
- Decreased installation and maintenance time, equals savings.
- Removeable interior tie down bracket, for ease of input cable installation



Ordering Guide





	Input Type
R1	Round 1 Grommet/3 Plugs
R2	Round 2 Grommets/2 Plugs
R3	Round 3 Grommets/1 Plug
R4	Round 4 Grommets/ 0 Plugs

XX

	Output Type
SA	Surelite IP SC/APC Simplex
SU	Surelite IP SC/UPC Simplex
LA	Surelite IP LC/APC Duplex
LU	Surelite IP LC/UPC Duplex

XX