

STARFIGHTER™

Select the correct Starfighter Dome to meet your needs!

SFOC	XXXX	-	X	-	X	-	X	-	X	-	X
		Dome Size (Max. Splices)	Splice Tray (# splices)		# Splice Trays		Mounting		# Cable Strain Relief Kits (fitting size)		# Ground Lugs
Starfighter Fiber Optic Closure	4024	4024-D (48 Single fusion)	A 612-SSTP 12 Splices	X	1-4	X	P = Pole/Wall A = Aerial D = ADSS	X	3-6 (3/4" Fitting)	X	0-5*
	4048	4048-D (96 Single fusion)	B 4048-SSTP 24 Splices	X	1-4	X	P = Pole/Wall A = Aerial D = ADSS	X	3-6 (3/4" Fitting)	X	0-5*
	4000	4000-D (192 Single fusion)	B 4048-SSTP 24 Splices	X	1-8	X	P = Pole/Wall A = Aerial D = ADSS	X	3-6 (1" Fitting)	X	0-6*
4000-D (288 Single fusion)		C 4072-SSTP 36 Splices									

*See notes

Example
SFOC4024-A-1-A-3-1

Grounding Lug Selection:

Selecting (0) grounding lugs will remove grounding braid from dome.
Selecting (1 or more) grounding lugs will include only (1) grounding braid.



Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com