

2.4GHz AirMax 2x2 MIMO Basestation Sector Antennas

Revolutionary, Cost/Performance Breakthrough Carrier Class MIMO BaseStation Antennas



AirMax Sector **2G-16-90**
Hi-gain 16dBi, 90deg.









AirMax Sector **2G-15-120**
Hi-Gain 15dBi, 120deg.

airMAX







MIMO TDMA Protocol System

TECHNICAL SPECIFICATIONS

Hi-Gain Airmax Sector 2G-90-16

Antenna and Electrical Characteristics		Return Loss	V-Pol Azimuth	V-Pol Elevation	H-Pol Azimuth	H-Pol Elevation	
	Frequency Range	2.3-2.7GHz					
	Gain	16.0-17.0dBi					
	Polarization	Dual Linear					
	Cross-pol Isolation	28dB min.					
	Max VSWR	1.5:1					
	Hpol Beamwidth (6dB)	91 deg.					
	Vpol Beamwidth (6dB)	90 deg.					
	Elevation Beamwidth	9 deg.					
	Electrical Downtilt	4 deg.					
	ETSI Specification	EN 302 326 DN2					
Dimensions	700x145x79mm						
Weight	3.9 kg						
Windloading	160 mph						

Hi-Gain Airmax Sector 2G-120-15

Antenna and Electrical Characteristics		Return Loss	V-Pol Azimuth	V-Pol Elevation	H-Pol Azimuth	H-Pol Elevation	
	Frequency Range	2.3-2.7GHz					
	Gain	15.0-16.0					
	Polarization	Dual Linear					
	Cross-pol Isolation	28dB min.					
	Max VSWR	1.5:1					
	Hpol Beamwidth (6dB)	123 deg.					
	Vpol Beamwidth (6dB)	118 deg.					
	Elevation Beamwidth	9 deg.					
	Electrical Downtilt	4 deg.					
	ETSI Specification	EN 302 326 DN2					
Dimensions	700x145x93 mm						
Weight	4.0 kg						
Windloading	160 mph						

Instantly pair with Rocket M2 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Mating bracket and weatherproof RF jumpers included.

