

PCFM

Agile FM Stereo Audio Modulator



- Frequency Range 88-108 MHz (FM Band)
- Microprocessor controlled digital phase-locked loop for solid drift-free output on any channel
- Agile push-button tuning and digital display for easy frequency selection
- 35dBmV adjustable output for optimum carrier-to-noise performance
- Switch-selectable between stereo and monaural operation
- Non-volatile memory for last channel recall in the event of power failure
- Signal-to-noise ratio >60 dB provides superior sound quality
- Front panel test point for easy RF level system monitoring
- Auxiliary AC outlet for convenience
- UL Approved

PCFM

Agile FM Stereo Audio Modulator

The **Pico Macom PCFM** is a frequency agile professional re-broadcast grade, microprocessor controlled Stereo/Mono Audio Modulator. Its phase-locked loop frequency control and sharp two-stage bandpass filtering minimize adjacent channel interference and assures accurate and spurious free output. The **PCFM** provides up to 35dBmV output across the FM band (88-108 MHz). The unit is easily tuned by using channel up/down buttons and the digital display located on the front panel. Designed specifically for commercial installations, the **PCFM** provides superior signal-to-noise ratio, discrete left-and-right audio signal separation, and enhanced dynamic range. Switchable mono/stereo capability provides FM transmission versatility. The modulator is shipped with all internal adjustments preset. **Pico Macom** backs up this product with its industry leading 5-year limited warranty.

Order From:




Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com

PCFM

Agile FM Stereo Audio Modulator



Front View



Rear View

Audio

Frequency Range:	88-108 MHz
Frequency Resolution:	200 kHz
Frequency Stability:	± 10 kHz
Audio Bandwidth:	30 Hz – 15 kHz
Audio S/N:	>60 dB
Audio Separation:	>30 dB
RF Output Level:	35 dBmV min
RF Level Adjustment:	10 dB

General

Power Input:	108 to 125 VAC, 60 Hz, 20W
Operating Temperature:	-10° to 50° C
Dimensions:	19"(L) x 3"(D) x 1 ³ / ₄ "(H)
Weight:	3.6 lbs.
Test Point:	-20dB
Connectors:	"F" type
Mounting:	Single 19" rack space

Ordering Information

PCFM

Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com