## COYOTE \* Taut Closure


## Refi nement of the Breed...

## A single closure that simplifies branch cable taps or repairs of taut fiber optic cables.

The 6.5" x 38" (165 x 965 mm) COYOTE Taut Closure organizes and protects up to 12 branch splices in either or both directions, or up to 12 pairs of fiber splices for repairing damaged cable.

The end plates are the innovative design used in the COYOTE Dome Closure and employ the easy to apply Gel Sealant System. Grommets available for the COYOTE Dome Closure can also be used for the COYOTE Taut Closure.

The unique mainframe assembly protects the fibers being "expressed" through the closure and organizes the splices on those fibers being spliced to the branch cables. Slack fibers from the branch cables or slack fibers between repair splices are stored in the center region of the mainframe.



Catalog Number	Description
8006947	6.5" x 38" (165 x 965 mm) COYOTE Taut Closure Kit

COYOTE Grommet Kits For use in COYOTE Dome, In-Line RUNT, Taut & Terminal Closures			
Cable Range Inches (mm)	Description	Splitting Location	
.4285 (10.7 - 21.6 mm)	2-entry grommet		
.4260 (10.7 - 15.2 mm)	1-entry grommet	(O) (E)	
.6085 (15.2 - 21.6 mm)	1-entry grommet		
.85 - 1.0 (21.6 - 25.4 mm)	1-entry grommet		
1.0 - 1.25 (25.4 - 31.6 mm)	1-entry grommet		
.4260 (10.7 - 15.2 mm)	2-entry grommet	(NIC. 40) (59)	
.3043 (7.6 - 10.9 mm)	4-entry grommet	600	
.12525 (3.2 - 6.4 mm)	6-entry grommet	0000	
.4260 (10.7 - 15.2 mm) .12525 (3.2 - 6.4 mm)	7-entry grommet	(2) (0) (0) (0) (0) (0) (0) (0) (0) (0) (0	
.12525 (3.2 - 6.4 mm)	8-entry grommet	0000	
	Cable Range Inches (mm)  .4285 (10.7 - 21.6 mm)  .4260 (10.7 - 15.2 mm)  .85 - 1.0 (21.6 - 25.4 mm)  1.0 - 1.25 (25.4 - 31.6 mm)  .4260 (10.7 - 15.2 mm)  .3043 (7.6 - 10.9 mm)  .12525 (3.2 - 6.4 mm)  .4260 (10.7 - 15.2 mm)	For use in COYOTE Dome, In-Line RUNT, Taut & Terminal Cable Range Inches (mm)         Description           .4285 (10.7 - 21.6 mm)         2-entry grommet           .4260 (10.7 - 15.2 mm)         1-entry grommet           .85 - 1.0 (21.6 - 25.4 mm)         1-entry grommet           1.0 - 1.25 (25.4 - 31.6 mm)         1-entry grommet           .4260 (10.7 - 15.2 mm)         2-entry grommet           .3043 (7.6 - 10.9 mm)         4-entry grommet           .12525 (3.2 - 6.4 mm)         6-entry grommet           .4260 (10.7 - 15.2 mm)         7-entry grommet	