



## STB-PDSD Standard Definition Cable Set-Top Box with CAS

### FEATURES

- Decodes MPEG-2 / AVC / H.264 / MPEG-4 video
- Decodes MPEG-1 Layer I/II and Dolby® AC-3 audio
- Clear QAM/Hollywood approved CAS
- Supports 64 and 256 QAM inputs
- Intuitive and simple to use interface
- Auto scanning for QAM channels and programs
- Supports Electronic Program Guide (EPG)
- Multiple language support
- Firmware updates via cable TV network
- Video output using analog composite video/audio
- PVR via external USB stick/drive
- RF loop through
- Remote control included



( Back Panel )



(PVR)

### SPECIFICATION

#### TUNER

QAM Modes	ITU-T J.83, Annex B
Constellation	64/256 QAM
Frequency	54MHz – 860MHz
RF Input Level	-25 dBm to -60 dBm

#### VIDEO

Decoder	AVC/H.264 HP@L4.1 MPEG-2 MP@HL MPEG-4 ASP supported Advance error concealment
Resolution	480i
Aspect Ratio	Auto, 16:9, 4:3 letter box, 4:3 pan scan

#### AUDIO

MPEG Decoder	MPEG layer I/II
AAC Decoder	AAC LC HE-AAC V1/V2, 5.1 down mix 2 ch
Dolby Digital	AC3 5.1

#### SECURITY

Conditional Access	Hollywood Approved CAS
--------------------	------------------------

#### FRONT PANEL

KEY	POWER, CH+, CH-
LED	GREEN (ON), RED (STBY)

#### REAR PANEL

RF Input	F-Type, 75ohm
RF loop through	F-Type, 75ohm
Composite Output	3 RCA (CVBS,A.left,A.right)
USB	USB 2.0
SPDIF	Coaxial

#### REMOTE CONTROL

Batteries	2 AAA type
-----------	------------

#### GENERAL

Power Adaptor Input	100V - 240V, 50/60Hz 0.35A
Power Adaptor Output	DC 5V, 2A
Composite Cables	Included
Power Consumption in Standby	<0.5W
Dimensions	4.53"(L) x 4.41"(D) x 1.38" (H)

### ORDERING INFORMATION

<b>STB-PDSD</b>	Standard Definition Cable Set-Top Box with CAS
<b>STB-CB</b>	High Definition Cable Set-Top Box with CAS

<b>STB-CB/RCU</b>	Remote Control for STB-CB/PDSD
<b>STB-PDSD/PS</b>	Power Supply for STB-PDSD