

DATA SHEET

CABLE GUIDE ROLLER - shaft

for shaft inlets or outlets - roller diameter Ø 130 mm

Item no.: 10157



VIDEO



Cable guide roller

Click here
Video



Detailed image:



DATA

ITEM NO	10157
DIMENSIONS	L 220.5 x W 155 x H 140 mm
LOAD BEARING CAPACITY	4.500 kg
WEIGHT	2.86 kg
MATERIAL	Roller: Aluminium Frame: Steel
ROLLER DIAMETER	Ø 130 mm
MAX. CABLE DIAMTER	Ø 100 mm
EAN-Code	9120045476385

ADVANTAGES

- ✓ Aluminium heavy-duty rollers with stainless steel ball bearings
- ✓ Robust metal frame
- ✓ CDP coating
- ✓ Ergonomic aluminium carrying handle
- ✓ Load capacity 4.500 kg

DESCRIPTION

The cable guide roller - shaft is ideally suited for mounting in shafts to pull cables gently around corners with the least possible resistance. It can be secured in place with screws via the assembly openings. The lightweight and highly robust design reduces the effort required with optimum success. The high-quality die-cast aluminium rollers with integrated ball bearing and the sturdy powder-coated steel frame guarantee a long service life. Ergonomic aluminium handle - Load capacity 4500 kg

Optimum area of application: to pull cables in shafts gently and effortlessly around corners

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 psc cable guide roller - shaft

INFORMATION

Optional accessories:

POLYESTER PULLING ROPE incl. reel

Rope: Ø 10 mm
Item no: 10167 - 120 m
Item no: 10168 - 200 m
Rope: Ø 12 mm
Item no: 10120 - 150 m
Item no: 10121 - 200 m
Item no: 10122 - 300 m
Item no: 10123 - 350 m



Related pulling system:

Capstan winch CW 800 E + trolley

Item no: 10138

