DATASHEET

RUNPO 5 - Profi -cable pulling system optimal for pipe diameters 16 mm - 40 mm Item no.: **10013** | **10014**



			Application examples:
RUNPO 5	Q- T RY	NPOS Kantenstativenten Kantenstativenten	Almost breakproof
Video Im	en on		Advantage over fiberglass
Achtung! Stromleitend Attention! electric conductive			Strand + pressing + RUNPOGLIDER
Stromleitend Attention! electric	Recomment	ded retail price / excluding VAT	Strand + pressing + RUNPOGLIDER
Stromleitend Attention! electric conductive	Recomment 10013	ded retail price / excluding VAT 10014	
Attention! electric conductive			ADVANTAGES • 50% less frictional resistance
Attention! electric conductive DATA ITEM NO.	10013	10014	ADVANTAGES • 50% less frictional resistance • 270 kg Total breaking load
Attention! Attention! Conductive DATA ITEM NO. LENGTH	10013 20 m	10014 30 m	ADVANTAGES
Attention! electric conductive DATA ITEM NO. LENGTH TOTAL WEIGHT	10013 20 m 1,06 kg	10014 30 m 1,30 kg	ADVANTAGES
Attention! electric conductive	10013 20 m 1,06 kg H 45 / B 315 / T 395	10014 30 m 1,30 kg	ADVANTAGES
Attention! Attention! electric conductive	10013 20 m 1,06 kg H 45 / B 315 / T 395 triple twisted specia	10014 30 m 1,30 kg	ADVANTAGES
Attention! Attention! electric conductive DATA ITEM NO. LENGTH TOTAL WEIGHT DIMENSIONS MATERIAL Ø ROD	10013 20 m 1,06 kg H 45 / B 315 / T 395 triple twisted specia 5,3 mm	10014 30 m 1,30 kg	ADVANTAGES
Attention! Attention! electric: conductive	10013 20 m 1,06 kg H 45 / B 315 / T 395 triple twisted specia 5,3 mm 15 mm	10014 30 m 1,30 kg	ADVANTAGES

DESCRIPTION

The RUNPO5 is another innovation by RUNPOTEC and a genuine "all-rounder". The patented viewfinder tip, the RUNPOGLEITER with twist compensation allows even the tightest radii to be overcome, with a total breaking load of an incredible 270 kg in relation to the entire pulling system. The special plastic strap with a diameter of 5.3 mm and a triple twist has an even better shearing effect than the 3 mm glass fibre rod; the frictional resistance is only half the normal value due to spot contact. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free. The RUNPO5 can be stowed in a very practical box in lengths of 20 m and 30 m. The 40 m RUNPO5 strap cannot be stored in the box.

Optimal field of application: for pipe dimensions 16 mm - 40 mm

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: RUNPO5 in plastic box - all RUNPO 5s are delivered from the factory with 2 x RUNPOGLEITER with twist compensation at the beginning and end of the spiral.

INFORMATION

the spiral

