



- Simultaneously strips the jacket, cores the dielectric, strips the aluminum sheath and trims the conductor to the proper length in one fast and precise operation on CommScope® Quantum Reach® Cable
- Specifically designed for CommScope® QR cables, also prepares Alcatel Cable Benelux – ACW cable
- Manual or drill operation; CST tools have a standard "T" handle with a built-in 3/8 inch (9.5mm) drill adapter; CST-R tools have a ratchet "T" handle and a separate 3/8 inch (9.5mm) drill adapter
- Heat treated, sheath cutting blade produces a smooth beveled edge and can be changed without the expense of replacing the entire coring bit
- Preset jacket blade assures there is no scoring or nicking of the aluminum sheath
- Rugged, durable all-metal construction
- Use of CC-100 or CC-200 Center Conductor Cleaner/Scraper removes residual dielectric remaining on the conductor after coring and stripping
- Not recommended for use on flooded cable
- Jacket Blade: CB 6667H
- Sheath Cutting Blade: CB 60
- Made in the U.S.A.
- Length: 7.50 in (190.5mm) Weight: 1 lbs 8 oz (675g)

## JCST-OR ORDERING GUIDE

Cable	Model Number Standard Handle	Model Number Ratchet Handle	Coring Bit Kit
320/7mm	JCST 7MMQR	JCST 7MMQR-R	CB164K
540	JCST 540QR	JCST 540QR-R	CB143K
715	JCST 715QR	JCST 715QR-R	CB159K
860	JCST 860QR	JCST 860QR-R	CB127K