

XPro LITE

Palm-Size Digital Multimeter

- Data Hold
- Easy-to-Read LCD Display

Overview

The XPro LITE™ Digital Multimeter from XFTP is an ideal tool for electrical maintenance. The multimeter measures AC/DC voltage, DC current, resistance, temperature, transistor and diode values, and electrical continuity. The multimeter features a convenient, large LCD screen and a data hold function. The XPro LITE Digital Multimeter comes complete with a battery, test leads, and a point contact temperature probe.



General Characteristics

Power	9 Volt battery (6F22)
LCD Display Size (H x W)	1.89" x 0.63" (48mm x 16mm)
Weight	0.34 lb (156 g)
Dimensions (H x W x D)	5.12" x 2.91" x 1.38" (130mm x 74mm x 35mm)

SPECIAL FUNCTIONS:

Diode measurement
Transistor measurement
Continuity buzzer
Data hold
Backlit display
Low battery indicator

INCLUDES THE FOLLOWING:

Test leads
Battery
Point contact temperature probe
Protective sleeve
User's manual



Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com

Specifications

BASIC FUNCTIONS	RANGE	RESOLUTION	ACCURACY*
DC Voltage	200 mV	100 µV	±(0.5% + 2)
	2 V	1 mV	±(0.5% + 2)
	20 V	10 mV	±(0.5% + 2)
	200 V	100 mV	±(0.5% + 2)
	500 V	1 V	±(0.8% + 2)
AC Voltage	200 V 500 V	100 mV 1V	±(1.2% + 10) ±(1.2% + 10)
DC Current	2 mA	1 µA	±(1.0% + 2)
	20 mA	10 µA	±(1.0% + 2)
	200 mA	100 µA	±(1.2% + 2)
	10 A	10 mA	±(2.0% + 5)
Resistance	200 Ω	0.1 Ω	±(0.8% + 5)
	2 KΩ	1 Ω	±(0.8% + 2)
	20 KΩ	10 Ω	±(0.8% + 2)
	200 KΩ	100 Ω	±(0.8% + 2)
	20 MΩ	10 KΩ	±(1.0% + 5)
Temperature	-40° to 150° C (-40° to 302° F)	1° C (1° F)	±(1.0% + 3) ±(1.0% + 4)
	150° to 1000° C (302° to 1832° F)	1° C (1° F)	±(1.5% + 15) ±(1.5% + 15)

* Accuracy ±(% + minimum resolution digits)

Input impedance for DC voltage measurement: approximately 10 MΩ



Order From:



Toll Free: 800-423-2594
www.multicominc.com
multicom@multicominc.com