

DATA SHEET

zNID 2600 Series Indoor GPON ONT: ZNID-GPON-2608T, 2624A, 2624P, 2625A, 2625P, 2628A, 2628P, 2628T, 2644A, 2644P, 2645A, 2645P, 2648A, 2648P, 2648



Features

- Standard ITU G.984 GPON
- Indoor deployment, but temperature-hardened for harsher environments
- Extended DC Power Range
- Triple-Play Services - VoIP, IP Video, HS Internet Access
- VoIP with CLASS 5 Features
- 802.3at PoE
- RF Video Output Option

Overview

DZS' indoor 2600 series GPON ONTs are standards-based CPEs designed for advanced triple-play deployments in home and business environments. These indoor models in DZS' zNID product line of ONTs provide a lower cost alternative to outdoor ONT solutions while providing unmatched flexibility in deployment.

Especially suited for FiberLAN applications, the 2600 series GPON ONTs are offered in a variety of models that include an RF Video port, 2 or 4 FXS POTS ports and up to 8 GE LAN ports which can provide PoE power for attached devices such as IP Phones, PTZ cameras, wireless access points, and remote switches. Extended operating temperatures and input voltages allow for creative deployments in areas and applications not possible with other ONTs.

The 2600 series GPON ONTs provide the same voice features found on the 2400 and 4200 series ONTs. Both MGCP and SIP are supported for direct connection to a VoIP Softswitch. This flexibility allows the ONTs to work in nearly all Telco networks, with interoperability support for a broad array of Softswitches.

The four or eight GE LAN ports can be separated into different services allowing the configuration of dedicated ports for IP video and data for one or more customers. Unique VLANs may be configured per customer to ensure full isolation of each customer's data traffic. The 2600 series GPON ONTs are ideally suited for Fiber-To-The-Desk applications where attached PoE devices can be powered directly from any or all of the ONT's four or eight PoE GE LAN ports simultaneously. Because up to four POTS ports are also available on the same ONT, legacy FAX machines, modems and analog phones can be conveniently connected.

With its extended power input range of 12 to 54 VDC standard on all 2600 series ONT models, new Fiber-To-The-Room applications are now possible where a single, centralized 48 VDC supply in a basement or closet can power all of the ONTs in an hotel or apartment complex using existing telephone or Ethernet wiring, without suffering excessive IR losses. Delivering high speed data, voice, and television to each room throughout the complex regardless of distance, just became easier.

The temperature-hardened 2600 series GPON ONTs are also well-suited for harsher environments such as unheated but weatherproof outside enclosures, or mounting under a roof in areas that are not temperature controlled. Other indoor ONTs are not rated to operate in such conditions.

The 2600 series GPON ONTs can be either wall mounted inside the home or placed freestanding on a desktop, and can use the same optional fiber tray as the 2400 series ONTs. A variety of battery backup options are available for maintaining lifeline services during AC power outages

Flexible management means the ONTs may be provisioned using the same intuitive Web interface and CLI as the 2400 and 4200 series ONTs, as well as through GPON-standard OMCI, and the DZS Network Management System (ZMS) using Unified Service Provisioning (USP). Software upgrades and configuration backups can be handled automatically by the ZMS using the CPE Manager feature. Management using a TR-069 compliant ACS will also be possible.

DZS provides the complete PON solution: ONT, OLT, splitter, EDFA, RF Transmitters, and cabinet solutions are available allowing our customers to buy a complete and fully tested solution from one trusted source.

ZNID 2600 SERIES INDOOR GPON ONT: ZNID-GPON-2608T, 2624A, 2624P, 2625A, 2625P, 2628A, 2628P, 2628T, 2644A, 2644P, 2645A, 2645P, 2648A, 2648P, 2648

Specifications

WEIGHT & DIMENSIONS

- 1.0 – 1.2LB (0.45 – 0.54 kg)
- Complete Enclosure
- 1.5 in. H x 10 in. W x 6 in. D
- 3.8 cm H x 25.4 cm W x 15.2 cm D

POWER

- 12-54 VDC +/- 6% (non-PoE models)
- 48-54 VDC +/- 6% (PoE models)
- 100-240 VAC 50/60 Hz (AC Adapter)
- Max Power (ONT only): 20W
- Max PoE Power for attached devices: 120W

INTERFACES

GPON

- SC/APC connector
- TU-T G.984 compliance (at levels down to -25 dBm)

GPON Tx

- 1310nm optics
- DBM (Differential Burst Mode)
- Upstream Data Rate: 1.25 Gbps
- Launch Power: +0.5dBm to +5.0dBm

GPON Rx

- 1490nm optics
- APD/TIA CW mode
- Downstream Data Rate: 2.50 Gbps
- Receiver Sensitivity: -28dBm
- Input Power Overload: -8dBm
- Input Damage Level: +5dBm
- RF Video Rx
- 1550nm optics
- Usable Input Power Range: -8dBm to +2dBm
- Input Power Overload: +2dBm
- Input Damage Level: +5dBm

Ethernet

- RJ-45 connector
- 4 or 8 x 10/100/1000 Base-T ports, all of which
- can support PoE
- Meets IEEE 802.3 specifications
- Auto-MDI/MDIX and auto speed supported

POTS

- RJ-11 connector
- 0, 2 or 4 FXS ports
- 2 Y-adapters included for 4-port models

RF Video Output Port

- 1xF-type connector
- RF Output Impedance: 75 ohms
- RF Output Level: 17dBmV min.
- RF Passband: 47 MHz – 1002 MHz

STANDARDS SUPPORT

GPON

- ITU-T G.984 compliant (at levels down to -25 dBm)

PoE

- 802.3at compliant (30W max per port, 120 W max per ONT)

VOICE SUPPORT

- SIP (RFC 3261)
- MGCP
- Codec: G.711 (u-law and A-law), G.729B, G726
- DTMF dialing
- 5 REN (total) per ONT
- Echo cancellation
- Voice Activity Detection and Comfort Noise Insertion
- Caller ID, Call Waiting, Call Forwarding, Call Transfer, Three Way
- Calling, Distinctive Ringing
- G.711 fallback for FAX
- T.30 and T.38 FAX
- DHCP client or static IP configuration

ZNID 2600 SERIES INDOOR GPON ONT: ZNID-GPON-2608T, 2624A, 2624P, 2625A, 2625P, 2628A, 2628P, 2628T, 2644A, 2644P, 2645A, 2645P, 2648A, 2648P, 2648

Specifications

PROTOCOL SUPPORT

GPON

- Fully ITU-T G.984 compliant framing
- 32 T-CONTs per device
- 32 GEM Ports per device
- Activation with automatic discovered SN and password in conformance with ITU-T G.984.3
- AES-128 Decryption with key generation and switching
- FEC (Forward Error Correction)
- 802.1p mapper service profile on U/S
- Support for Multicast GEM Port QoS
- Ethernet bridging/switching per IEEE 802.1d/802.1q
- Traffic management (priority queuing and traffic shaping)
- QoS with support for IEEE 802.1p + DSCP VLANS
- Per port IEEE 802.1q VLAN ID processing
- VLAN tagging/untagging
- VLAN Stacking (QinQ)
- VLAN Switching

IPTV

- IGMP v2 Snooping
- VLAN support

Layer 2

- 802.3n flow control
- Automatic MAC learning and aging
- Support for up to 4,096 MAC addresses for RG traffic flows
- Broadcast storm control

IP Routing and Firewall

- PPPoE
- NAT/NAPT
- port forwarding
- DHCP Server
- DNS Proxy

MANAGEMENT

- OMCI
- Web UI
- CLI
- SNMP
- TR-069
- USP (Unified Service Provisioning)

REGULATORY COMPLIANCE

- CE
- UL
- FCC part B

OPERATING REQUIREMENTS

- Temperature: -40°C to +60°C
- Humidity: 5% to 90% RH, non-condensing



Ordering Information

MODEL	DESCRIPTION
ZNID-GPON-2608T-xx	Indoor GPON ONT, 0xPOTS, 8xGE(PoE); xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2624A-xx	Indoor GPON ONT, 2xPOTS, 4xGE; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2624P-xx	Indoor GPON ONT, 2xPOTS, 4xGE(PoE); xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2625A-xx	Indoor GPON ONT, 2xPOTS, 4xGE(PoE), RF Video; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2625P-xx	Indoor GPON ONT, 2xPOTS, 4xGE(PoE), RF Video; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2628A-xx	Indoor GPON ONT, 2xPOTS, 8xGE; xx= 00 (none), NA, UK, EU power supply
ZNID-GPON-2628P-xx	Indoor GPON ONT, 2xPOTS, 4xGE(PoE) + 4xGE; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2628T-xx	Indoor GPON ONT, 2xPOTS, 8xGE(PoE); xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2644A-xx	Indoor GPON ONT, 4xPOTS, 4xGE; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2644P-xx	Indoor GPON ONT, 4xPOTS, 4xGE(PoE); xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2645A-xx	Indoor GPON ONT, 4xPOTS, 4xGE(PoE), RF Video; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2645P-xx	Indoor GPON ONT, 4xPOTS, 4xGE(PoE), RF Video; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2648A-xx	Indoor GPON ONT, 4xPOTS, 8xGE; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2648P-xx	Indoor GPON ONT, 4xPOTS, 4xGE(PoE) + 4xGE; xx = 00 (none), NA, UK, EU power supply
ZNID-GPON-2648T-xx	Indoor GPON ONT, 4xPOTS, 8xGE(PoE); xx = 00 (none), NA, UK, EU power supply