

Compression Assembly Tools

• Tools designed for 6 & 59 compression connectors

Field proven - high strength cast aluminum body

Tools provide a clear view of the connector assembly compression action

 Spring loaded, split jaws position the cable and connector for easy insertion and removal

- · Ergonomic, user friendly design
- US Patent #5,934,137
- Approx. length: 7 in (178 mm);
 Approx. weight: 1 lb (454 g)




- Configured with the new "Universal" plunger tip, factory preset and calibrated to assemble the following connectors:
 - Telewire Digicon-S™, Gilbert ULTRASEAL™, PPC EX XL
 - Thomas & Betts SNAP-N-SEAL®, PCT DRS
- Plunger tip can be changed out to allow assembly of other compression connectors (EZF*, EX, SPL, and TAC)
- · Calibration/ gage block and hex wrench supplied with tool

CAT - Universal-FX

- FX model tool has same new "Universal" plunger tip as the Universal Model but is "fixed" (plunger tip factory set, calibrated, and non-adjustable)
- Assembles the same connectors as the CAT-UNIVERSAL
- FX model does not allow future plunger tip changeover

Other CAT Models

- Tools factory preset and calibrated to assemble either EX, EZF®, SPL or TAC connectors
- Color coded plunger tip band and tool label for easy connector identification
- Plunger tip can be changed to allow assembly of any other compression connector
- Calibration/ gage block and hex wrench supplied with tool



^{*}CAT-EZF is factory set for series 6 EZF * connectors and includes a gage block for series 59 EZF * connectors.

^{**}Plunger tip kits come with tip, gage block, hex wrench, set screw