

# OmniSmart UPS System

Line-interactive, medical-grade battery backup



## Model #: OMNISMART350HG

- ▶ UL 2601-1 listed
- ▶ 330VA line interactive tower UPS system with less than 300 microamps leakage
- ▶ Hospital-grade plug and 4 hospital-grade NEMA5-15R output receptacles
- ▶ Corrects brownouts as low as 83V without using battery power
- ▶ Built-in DB9 communications port
- ▶ 2 line phone suppression for TEL/DSL line protection

## DESCRIPTION

---

Tripp Lite's OMNISMART350HG offers medical-grade UPS protection with built-in line interactive voltage regulation, intelligent monitoring and unattended shutdown capability. Hospital-grade plug & outlets, plus built-in isolation transformer with faraday shield offers full isolation and removes common mode noise. UL 2601-1 listed as medical electrical equipment with less than 300 microamps cumulative leakage current for the UPS and all connected equipment. 330VA power handling capacity supports computers, internetworking equipment and other critical loads during commercial power failures. Line interactive voltage regulation corrects brownouts as low as 83V back to normal 120V levels, saving battery reserves for use only during complete power failures. Includes, 2 line phone surge suppression and built-in DB-9 communications port that works with PowerAlert Software and cabling to provide automatic unattended shutdown of connected network and PC applications.

## KEY BUYING POINTS

---

- Ideal UPS protection for applications in medical patient-care areas where UL2601-1 listed electrical medical equipment is required
- Maintains less than 300 microamps leakage current for UPS and all connected equipment
- Line-interactive voltage regulation corrects brownouts as low as 83V without using battery power
- Hospital-grade plug and outlets offer added degree of safety and reliability to input/output connections
- Full line isolation prevents shock potential and operational problems in sensitive electronic equipment
- Resistant to electrostatic discharge
- Supports loads up to 330VA / 225 watts
- 46 minutes half load runtime (with 165VA load), 18 minutes full load runtime (with 330VA load)
- 4 protected hospital-grade outlets; 6-ft. cord
- 1-DB9 serial port for network interface; SNMP compatible
- Complete surge protection, line isolation and EMI/RFI noise filtering
- 2 phone line surge suppression for modems, fax machines and other phone accessories
- 2 year product warranty
- Complete remote monitoring cabling included, PowerAlert UPS management software available via free download
- 4 diagnostic LEDs indicate AC present, on battery, voltage correction & battery low/replace
- Battery replacement door
- Grounding lug

---

●

---