



## Product Description

SEALPIC cables are designed primarily for aerial use. In this application, the cable must be attached to a support strand. If the cable is to be placed in a duct, the cable must be pressurized.

## Physical Description

- **CONDUCTORS:** Solid annealed copper in 19, 22, 24 and 26 AWG.
- **INSULATION:** Conductors are insulated with solid polyolefin, color coded in accordance with industry standards.
- **TWISTED PAIRS:** Individual insulated conductors are twisted into pairs with varying lay lengths to minimize crosstalk and specific color combinations to provide pair identification.
- **CORE ASSEMBLY:** Cables of 25 pairs or less are assembled into a cylindrical core. Cables larger than 25 pairs are assembled into units, which are then used to assemble the core. Units are individually identifiable by color coded unit binders.
- **CORE WRAP:** A non-hygroscopic, dielectric tape is applied over the core assembly to provide protection for the core.
- **SHIELDING:** A corrugated, copolymer coated, 8-mil aluminum tape is applied longitudinally with an overlap.
- **JACKET:** A black, linear low-density polyethylene jacket is applied overall. The jacket provides a tough protective covering designed to withstand exposure to direct sunlight, atmospheric temperature changes and stresses expected in standard installations.
- **JACKET MARKINGS:** Information such as manufacturer's identification, pair count, AWG, product identification, sequential footage and a telephone handset is printed at 2 ft. intervals on the cable jacket.

## Electrical Specifications

### Average Mutual Capacitance at 1000 Hz

Total Number of Pairs	nF/mile	nF/km
12 or less	83 ± 7	52 ± 4
Over 12	83 ± 4	52 ± 2

Conductor Size		Minimum Insulation Resistance 68° F (20° C)		Max Average Attenuation 772 kHz @ 68° F (20° C)		Max Conductor Resistance @ 68° F (20° C) Ohms/sheath		DC Resistance Unbalance Maximum %		Dielectric Strength DC Potential – Volts	
AWG	mm	gigohm-mile	gigohm-km	dB/kft	dB/km	mile	km	Avg.	Individual Pair	Cdr. to Cdr.	Cdr. to Grnd.
19	0.90	1.0	1.6	3.3	10.9	45.0	28.0	1.5	5.0	5,000	10,000
22	0.64	1.0	1.6	4.6	15.3	91.0	56.5	1.5	5.0	4,000	10,000
24	0.50	1.0	1.6	5.7	19.4	144.0	89.5	1.5	5.0	3,000	10,000
26	0.40	1.0	1.6	7.2	23.6	232.0	144.2	1.5	5.0	2,400	10,000

Minimum Near End Crosstalk (NEXT) at	150 kHz		772 kHz		Capacitance Unbalance Pair to Pair @ 1 kHz		Maximum Individual		Maximum RMS	
	P.S. WUNEXT mean (dB)	P.S. WUNEXT worst pair (dB)			Pairs		pF/kft	pF/km	pF/kft	pF/km
	58	53			12 or less		80	145	-	-
					more than 12		80	145	25	45

Minimum Far End Crosstalk at 150 kHz				
Conductor size (AWG)	19	22	24	26
P.S. ELFEXT mean (dB/kft)	65	63	63	61
P.S. ELFEXT worst pair (dB/kft)	59	57	57	57

Minimum Far End Crosstalk at 772 kHz				
Conductor size (AWG)	19	22	24	26
P.S. ELFEXT mean (dB/kft)	51	49	49	47
P.S. ELFEXT worst pair (dB/kft)	45	43	43	43

Capacitance Unbalance Pair to Ground @ 1 kHz	Maximum Individual		Maximum Avg	
	Pairs		pF/kft	pF/km
12 or less			800	2625
more than 12			800	2625
			175	574

\*For cables of 12 pairs or less, the maximum average attenuation may be increased by 10% over the values shown.

Available through **Multicom, Inc.**  
1076 Florida Central Parkway, Longwood, FL 32750

## Part Numbers and Physical Characteristics

	Part #	Pair Count	Nom. OD inches (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Approx. Shipping Weight lbs (kg)	Reel Size FxTxD (in)
<b>19 AWG</b> (0.90 mm)	01-026-40	6	0.48 (12)	105 (155)	5000 (1524)	635 (285)	44 x 18 x 20
	01-028-40	12	0.57 (15)	170 (255)	5000 (1524)	1015 (460)	46 x 25 x 20
	01-031-40	25	0.76 (19)	310 (460)	5000 (1524)	1755 (795)	52 x 25 x 20
	01-034-40	50	1.00 (25)	575 (855)	5000 (1524)	3165 (1435)	62 x 30 x 24
	01-038-40	100	1.34 (34)	1075 (1600)	5000 (1524)	6075 (2755)	78 x 40 x 39
<b>22 AWG</b> (0.64 mm)	01-057-40	6	0.39 (9.9)	65 (95)	5000 (1524)	390 (175)	36 x 18 x 14
	01-059-40	12	0.46 (12)	100 (150)	5000 (1524)	610 (275)	44 x 18 x 20
	01-062-40	25	0.60 (15)	180 (270)	5000 (1524)	1065 (485)	46 x 25 x 20
	01-065-40	50	0.77 (20)	315 (470)	5000 (1524)	1780 (805)	52 x 25 x 20
	01-069-40	100	1.02 (26)	580 (865)	5000 (1524)	3190 (1445)	62 x 30 x 24
	01-073-40	200	1.38 (35)	1095 (1630)	5000 (1524)	6175 (2800)	78 x 40 x 39
	01-075-40	300	1.66 (42)	1605 (2390)	2500 (762)	4625 (2100)	72 x 35 x 36
	01-077-40	400	1.89 (48)	2115 (3150)	2500 (762)	5985 (2715)	78 x 40 x 39
	01-081-40	600	2.28 (58)	3125 (4650)	1250 (381)	4520 (2050)	72 x 35 x 36
	01-083-40	900	2.76 (70)	4635 (6900)	1250 (381)	6590 (2990)	84 x 40 x 42
	01-085-40	1200	3.15 (80)	6125 (9115)	1000 (305)	6920 (3140)	84 x 40 x 42
	<b>24 AWG</b> (0.50 mm)	01-092-40	6	0.35 (8.9)	50 (75)	5000 (1524)	295 (135)
01-094-40		12	0.41 (10)	75 (110)	5000 (1524)	440 (200)	36 x 18 x 14
01-097-40		25	0.51 (13)	125 (185)	5000 (1524)	735 (330)	44 x 18 x 20
01-100-40		50	0.64 (16)	215 (320)	5000 (1524)	1240 (560)	46 x 25 x 20
01-104-40		100	0.83 (21)	385 (575)	5000 (1524)	2170 (985)	58 x 25 x 20
01-108-40		200	1.12 (28)	715 (1065)	5000 (1524)	4190 (1900)	72 x 35 x 36
01-110-40		300	1.33 (34)	1040 (1550)	5000 (1524)	5900 (2675)	78 x 40 x 39
01-112-40		400	1.52 (39)	1360 (2025)	2500 (762)	4015 (1820)	72 x 35 x 36
01-116-40		600	1.82 (46)	2005 (2985)	2500 (762)	5710 (2590)	78 x 40 x 39
01-118-40		900	2.19 (56)	2960 (4405)	1250 (381)	4315 (1955)	72 x 35 x 36
01-120-40		1200	2.49 (63)	3895 (5795)	1250 (381)	5570 (2525)	78 x 40 x 39
01-121-40		1500	2.79 (71)	4845 (7210)	1250 (381)	6855 (3110)	84 x 40 x 42
01-124-40		1800	3.04 (77)	5785 (8610)	1000 (305)	6485 (2940)	78 x 40 x 39
01-125-40		2100	3.31 (84)	6735 (10025)	1000 (305)	7530 (3415)	84 x 40 x 42
01-126-40		2400	3.49 (89)	7650 (11385)	750 (229)	6915 (3135)	96 x 40 x 48
<b>26 AWG</b> (0.40 mm)		01-132-40	25	0.44 (11)	90 (135)	5000 (1524)	515 (235)
	01-135-40	50	0.55 (14)	150 (225)	5000 (1524)	915 (415)	46 x 25 x 20
	01-139-40	100	0.70 (18)	260 (385)	5000 (1524)	1505 (680)	52 x 25 x 20
	01-143-40	200	0.93 (24)	475 (705)	5000 (1524)	2745 (1245)	65 x 30 x 32
	01-145-40	300	1.07 (27)	680 (1010)	5000 (1524)	4015 (1820)	72 x 35 x 36
	01-147-40	400	1.23 (31)	880 (1310)	5000 (1524)	5100 (2315)	78 x 40 x 39
	01-151-40	600	1.47 (37)	1295 (1925)	5000 (1524)	7270 (3300)	84 x 40 x 42
	01-153-40	900	1.75 (45)	1895 (2820)	2500 (762)	5435 (2465)	78 x 40 x 39
	01-155-40	1200	2.00 (51)	2495 (3715)	2500 (762)	6935 (3145)	78 x 40 x 39
	01-156-40	1500	2.25 (57)	3095 (4605)	1250 (381)	4485 (2035)	72 x 35 x 36
	01-157-40	1800	2.44 (62)	3690 (5490)	1250 (381)	5310 (2410)	78 x 40 x 39

**Standards Compliance:**

**ANSI/ICEA S-85-625-2002; Formerly manufactured to RDUP Specification PE-22 (PE-22 was deactivated by RDUP and is superseded by ANSI/ICEA specifications), RoHS compliant.**

Available through **Multicom, Inc.**  
1076 Florida Central Parkway, Longwood, FL 32750

www.multicominc.com

Ph: 407-331-7779 Toll Free: 800-423-2594 Fax: 407-339-0204

multicom@multicominc.com